

tf.compat.v1.sparse_placeholder Stay organized with collections Save and categorize content based on your preferences.

https://www.tensorflow.org/api_docs/python/tf/compat/v1/sparse_placeholder

Inserts a placeholder for a sparse tensor that will be always fed.

Function Signatures

```
tf.compat.v1.sparse_placeholder( dtype, shape=None, name=None
)
```

Code Examples

```
tf.compat.v1.sparse_placeholder(  
dtype, shape=None, name=None  
)
```

```
tf.compat.v1.sparse_placeholder(  
dtype, shape=None, name=None  
)
```

```

x = tf.compat.v1.sparse.placeholder(tf.float32)
y = tf.sparse.reduce_sum(x)
with tf.compat.v1.Session() as sess:
    print(sess.run(y)) # ERROR: will fail because x was not fed.
    indices = np.array([[3, 2, 0], [4, 5, 1]], dtype=np.int64)
    values = np.array([1.0, 2.0], dtype=np.float32)
    shape = np.array([7, 9, 2], dtype=np.int64)
    print(sess.run(y, feed_dict={
x: tf.compat.v1.SparseTensorValue(indices, values, shape)})) #
Will
succeed.
    print(sess.run(y, feed_dict={
x: (indices, values, shape)})) # Will succeed.
    sp = tf.sparse.SparseTensor(indices=indices, values=values,
dense_shape=shape)
    sp_value = sp.eval(session=sess)
    print(sess.run(y, feed_dict={x: sp_value})) # Will succeed.

```

```

x = tf.compat.v1.sparse.placeholder(tf.float32)
y = tf.sparse.reduce_sum(x)
with tf.compat.v1.Session() as sess:
    print(sess.run(y)) # ERROR: will fail because x was not fed.
    indices = np.array([[3, 2, 0], [4, 5, 1]], dtype=np.int64)
    values = np.array([1.0, 2.0], dtype=np.float32)
    shape = np.array([7, 9, 2], dtype=np.int64)
    print(sess.run(y, feed_dict={
x: tf.compat.v1.SparseTensorValue(indices, values, shape)})) #
Will
succeed.
    print(sess.run(y, feed_dict={
x: (indices, values, shape)})) # Will succeed.
    sp = tf.sparse.SparseTensor(indices=indices, values=values,
dense_shape=shape)
    sp_value = sp.eval(session=sess)
    print(sess.run(y, feed_dict={x: sp_value})) # Will succeed.

```

Documentation

Inserts a placeholder for a sparse tensor that will be always fed.

View aliases

Compat aliases for migration

See

Migration guide for
more details.

`tf.compat.v1.sparse.placeholder`

Migrate to TF2

This API is not compatible with eager execution and `tf.function`. To migrate to TF2, rewrite the code to be compatible with eager execution. Check the migration guide

on replacing `Session.run` calls. In TF2, you can just pass tensors directly into ops and layers. If you want to explicitly set up your inputs, also see Keras functional API on

how to use `tf.keras.Input` to replace `tf.compat.v1.sparse_placeholder`.

`tf.function` arguments also do the job of `tf.compat.v1.sparse_placeholder`.

For more details please read Better performance with `tf.function`.

Description

Used in the notebooks

- Universal Sentence Encoder-Lite demo

For example:

Returns

Raises