

tf.compat.v1.sparse_reduce_sum Stay organized with collections Save and categorize content based on your preferences.

https://www.tensorflow.org/api_docs/python/tf/compat/v1/sparse_reduce_sum

*Computes `tf.sparse.add` of elements across dimensions of a `SparseTensor`.
(deprecated arguments) (deprecated arguments)*

Function Signatures

```
tf.compat.v1.sparse_reduce_sum( sp_input, axis=None,  
keepdims=None, reduction_axes=None, keep_dims=None )  
(keep_dims)  
(reduction_axes)
```

Code Examples

```
tf.compat.v1.sparse_reduce_sum(  
sp_input, axis=None, keepdims=None, reduction_axes=None,  
keep_dims=None  
)
```

```
tf.compat.v1.sparse_reduce_sum(  
    sp_input, axis=None, keepdims=None, reduction_axes=None,  
    keep_dims=None  
)
```

```
x = tf.sparse.SparseTensor([[0, 0], [0, 2], [1, 1]], [1, 1, 1], [2,  
3])  
tf.sparse.reduce_sum(x)  
  
tf.sparse.reduce_sum(x, 0)  
  
tf.sparse.reduce_sum(x, 1) # Can also use -1 as the axis  
  
tf.sparse.reduce_sum(x, 1, keepdims=True)  
  
tf.sparse.reduce_sum(x, [0, 1])
```

```
x = tf.sparse.SparseTensor([[0, 0], [0, 2], [1, 1]], [1, 1, 1], [2,  
3])
```

```
tf.sparse.reduce_sum(x)
```

```
tf.sparse.reduce_sum(x, 0)
```

Documentation

Computes `tf.sparse.add` of elements across dimensions of a `SparseTensor`.
(deprecated arguments) (deprecated arguments)

View aliases

Compat aliases for migration

See

Migration guide for
more details.

`tf.compat.v1.sparse.reduce_sum`

This is the reduction operation for the elementwise `tf.sparse.add` op.

This Op takes a `SparseTensor` and is the sparse counterpart to `tf.reduce_sum()`. In particular, this Op also returns a dense `Tensor` instead of a sparse one.

Reduces `sp_input` along the dimensions given in `reduction_axes`. Unless `keepdims` is true, the rank of the tensor is reduced by 1 for each entry in `reduction_axes`. If `keepdims` is true, the reduced dimensions are retained with length 1.

If `reduction_axes` has no entries, all dimensions are reduced, and a tensor with a single element is returned. Additionally, the axes can be negative, similar to the indexing rules in Python.

For example

Returns

