

tf.control_dependencies Stay organized with collections Save and categorize content based on your preferences.

https://www.tensorflow.org/api_docs/python/tf/control_dependencies

Wrapper for Graph.control_dependencies() using the default graph.

Function Signatures

```
Graph.control_dependencies()  
tf.control_dependencies( control_inputs ) ->  
Graph._ControlDependenciesController
```

Code Examples

```
tf.control_dependencies(  
    control_inputs  
) -> Graph._ControlDependenciesController
```

```
tf.control_dependencies(  
    control_inputs  
) -> Graph._ControlDependenciesController
```

```
@tf.function(  
input_signature=[tf.TensorSpec([None, None], tf.float32),  
tf.TensorSpec([None, None], tf.float32)])  
def my_assert_func_1(x, bias):  
# `tf.function` attempts to execute `tf.math.add` in parallel to  
# `assert_equal`. As a result an error can get raised from  
`tf.math.add`  
# without triggering the assertion error.  
tf.assert_equal(tf.shape(x)[1],  
tf.shape(bias)[1],  
message='bad shape')  
return x + bias
```

```
@tf.function(  

```

```
input_signature=[tf.TensorSpec([None, None], tf.float32),
```

```
tf.TensorSpec([None, None], tf.float32)])
```

```
def my_assert_func_1(x, bias):
```

```
# `tf.function` attempts to execute `tf.math.add` in parallel to
```

Documentation

Wrapper for `Graph.control_dependencies()` using the default graph.

View aliases

Compat aliases for migration

See

Migration guide for
more details.

`tf.compat.v1.control_dependencies`

Used in the notebooks

- Bayesian Modeling with Joint Distribution
 - TensorFlow Probability Case Study: Covariance Estimation

See `tf.Graph.control_dependencies` for more details.

In TensorFlow 2 with eager and/or Autograph, you should not need this method most of the times, as ops execute in the expected order thanks to automatic control dependencies. Only use it to manually control ordering, for example as a workaround to known issues such as `tf.function` with `tf.debugging.assert*` and `tf.py_function`.

For example:

When eager execution is enabled, any callable object in the `control_inputs` list will be called.

Returns