

tf.convert_to_tensor Stay organized with collections Save and categorize content based on your preferences.

https://www.tensorflow.org/api_docs/python/tf/convert_to_tensor

Converts the given value to a Tensor.

Function Signatures

```
tf.convert_to_tensor( value, dtype=None, dtype_hint=None,  
name=None ) -> tf.Tensor
```

Code Examples

```
tf.convert_to_tensor(  
value, dtype=None, dtype_hint=None, name=None  
) -> tf.Tensor
```

```
tf.convert_to_tensor(  
value, dtype=None, dtype_hint=None, name=None  
) -> tf.Tensor
```

```
import numpy as np  
def my_func(arg):  
    arg = tf.convert_to_tensor(arg, dtype=tf.float32)  
    return arg
```

```
import numpy as np
```

```
def my_func(arg):
```

```
    arg = tf.convert_to_tensor(arg, dtype=tf.float32)
```

Documentation

Converts the given value to a Tensor.

Used in the notebooks

- Logistic regression for binary classification with Core APIs
 - Extension types

- Matrix approximation with Core APIs
- TensorFlow basics
- Distributed training with Core APIs and DTensor
- DeepDream
- Custom training: walkthrough
- Distributed training with DTensors
- Load a pandas DataFrame
- Scalable model compression

This function converts Python objects of various types to Tensor objects. It accepts Tensor objects, numpy arrays, Python lists, and Python scalars.

For example:

This function can be useful when composing a new operation in Python (such as `my_func` in the example above). All standard Python op constructors apply this function to each of their Tensor-valued inputs, which allows those ops to accept numpy arrays, Python lists, and scalars in addition to Tensor objects.

Returns

`## Raises`