

tf.executing_eagerly Stay organized with collections Save and categorize content based on your preferences.

https://www.tensorflow.org/api_docs/python/tf/executing_eagerly

Checks whether the current thread has eager execution enabled.

Function Signatures

```
tf.executing_eagerly()
```

Code Examples

```
tf.executing_eagerly()
```

```
tf.executing_eagerly()
```

```
print(tf.executing_eagerly())  
True
```

```
print(tf.executing_eagerly())
```

```
@tf.function  
def fn():  
    with tf.init_scope():  
        print(tf.executing_eagerly())  
        print(tf.executing_eagerly())  
    fn()  
True  
False
```

```
@tf.function
```

Documentation

Checks whether the current thread has eager execution enabled.

Used in the notebooks

- Text classification with TensorFlow Hub: Movie reviews
 - Neural machine translation with attention
 - Fast Style Transfer for Arbitrary Styles
 - Text Classification with Movie Reviews
 - Graph regularization for sentiment classification using synthesized graphs

Eager execution is enabled by default and this API returns `True` in most of cases. However, this API might return `False` in the following use cases.

- Executing inside `tf.function`, unless under `tf.init_scope` or

`tf.config.run_functions_eagerly(True)` is previously called.

- Executing inside a transformation function for `tf.dataset`.
- `tf.compat.v1.disable_eager_execution()` is called.

General case:

Inside `tf.function`:

Inside `tf.function` after `tf.config.run_functions_eagerly(True)` is called:

Inside a transformation function for `tf.dataset`:

Returns

