

tf.fill Stay organized with collections

Save and categorize content based on your preferences.

https://www.tensorflow.org/api_docs/python/tf/fill

Creates a tensor filled with a scalar value.

Function Signatures

```
tf.fill( dims, value, name=None, layout=None )
```

Code Examples

```
tf.fill(  
    dims, value, name=None, layout=None  
)
```

```
tf.fill(  
    dims, value, name=None, layout=None  
)
```

```
tf.fill([2, 3], 9)
```

```
tf.fill([2, 3], 9)
```

```
array([[9, 9, 9],
```

```
[9, 9, 9]], dtype=int32)>
```

Documentation

Creates a tensor filled with a scalar value.

View aliases

Compat aliases for migration

See

Migration guide for
more details.

`tf.compat.v1.fill`

Used in the notebooks

- Ragged tensors

- `tf.data`: Build TensorFlow input pipelines
- Subword tokenizers
- Unicode strings
- Scalable model compression
- Multiple changepoint detection and Bayesian model selection
- Graph-based Neural Structured Learning in TFX
- Graph regularization for sentiment classification using synthesized graphs
- Bayesian Gaussian Mixture Model and Hamiltonian MCMC

See also `tf.ones`, `tf.zeros`, `tf.one_hot`, `tf.eye`.

This operation creates a tensor of shape `dims` and fills it with `value`.

For example:

`tf.fill` evaluates at graph runtime and supports dynamic shapes based on other runtime `tf.Tensor`s, unlike `tf.constant(value, shape=dims)`, which embeds the value as a `Const` node.

Returns

`## Raises`

numpy compatibility

Similar to `np.full`. In numpy, more parameters are supported. Passing a number argument as the shape (`np.full(5, value)`) is valid in numpy for specifying a 1-D shaped result, while TensorFlow does not support this syntax.

