

tf.foldl Stay organized with collections Save and categorize content based on your preferences.

https://www.tensorflow.org/api_docs/python/tf/foldl

*foldl on the list of tensors unpacked from elems on dimension 0.
(deprecated argument values)*

Function Signatures

```
tf.foldl( fn, elems, initializer=None,  
parallel_iterations=10, back_prop=True, swap_memory=False,  
name=None )  
(back_prop=False)
```

Code Examples

```
tf.foldl(  
    fn,  
    elems,  
    initializer=None,  
    parallel_iterations=10,  
    back_prop=True,  
    swap_memory=False,  
    name=None  
)
```

```
tf.foldl(  
    fn,  
    elems,  
    initializer=None,  
    parallel_iterations=10,  
    back_prop=True,  
    swap_memory=False,  
    name=None  
)
```

```
elems = tf.constant([1, 2, 3, 4, 5, 6])  
sum = tf.foldl(lambda a, x: a + x, elems)  
# sum == 21
```

```
elems = tf.constant([1, 2, 3, 4, 5, 6])  
sum = tf.foldl(lambda a, x: a + x, elems)  
# sum == 21
```

Documentation

`foldl` on the list of tensors unpacked from `elems` on dimension 0. (deprecated argument values)

This `foldl` operator repeatedly applies the callable `fn` to a sequence of elements from first to last. The elements are made of the tensors unpacked from `elems` on dimension 0. The callable `fn` takes two tensors as arguments. The first argument is the accumulated value computed from the preceding invocation of `fn`, and the second is the value at the current position of `elems`. If `initializer` is `None`, `elems` must contain at least one element, and its first element is used as the initializer.

Suppose that `elems` is unpacked into `values`, a list of tensors. The shape of the result tensor is `fn(initializer, values[0]).shape``.

This method also allows multi-arity `elems` and output of `fn`. If `elems` is a (possibly nested) list or tuple of tensors, then each of these tensors must have a matching first (unpack) dimension. The signature of `fn` may match the structure of `elems`. That is, if `elems` is `(t1, [t2, t3, [t4, t5]])`, then an appropriate signature for `fn` is:
`fn = lambda (t1, [t2, t3, [t4, t5]]):`

Returns

`## Raises`

`## Example`