

tf.get_logger Stay organized with collections Save and categorize content based on your preferences.

https://www.tensorflow.org/api_docs/python/tf/get_logger

Return TF logger instance.

Function Signatures

```
tf.get_logger()  
tf.get_logger().error("The value %d is invalid.", 3)
```

Code Examples

```
tf.get_logger()
```

```
tf.get_logger()
```

```
tf.get_logger().error("The value %d is invalid.", 3)
```

```
tf.get_logger().error("The value %d is invalid.", 3)
```

```
tf.get_logger().setLevel(ERROR)  
tf.get_logger().warn("This is a warning.")
```

```
tf.get_logger().setLevel(ERROR)
```

```
tf.get_logger().warn("This is a warning.")
```

Documentation

Return TF logger instance.

View aliases

Compat aliases for migration

See

Migration guide for
more details.

`tf.compat.v1.get_logger`

Used in the notebooks

- Migrating your TFLite code to TF2
 - Customizing MinDiffModel
 - Integrating MinDiff with MinDiffModel
 - Integrating MinDiff without MinDiffModel
 - Subword tokenizers
 - TensorFlow Hub Object Detection Colab
 - Implement Differential Privacy with TensorFlow Privacy
 - Parametrized Quantum Circuits for Reinforcement Learning
 - Object Detection with TensorFlow Lite Model Maker
 - Text classification with TensorFlow Lite Model Maker

Returns

See Python documentation (<https://docs.python.org/3/library/logging.html>)

for detailed API. Below is only a summary.

The logger has 5 levels of logging from the most serious to the least:

- FATAL
- ERROR
- WARN
- INFO
- DEBUG

The logger has the following methods, based on these logging levels:

- `fatal(msg, *args, **kwargs)`
- `error(msg, *args, **kwargs)`
- `warn(msg, *args, **kwargs)`
- `info(msg, *args, **kwargs)`
- `debug(msg, *args, **kwargs)`

The msg can contain string formatting. An example of logging at the ERROR level

using string formatting is:

You can also specify the logging verbosity. In this case, the WARN level log will not be emitted: