

tf.grad_pass_through Stay organized with collections Save and categorize content based on your preferences.

https://www.tensorflow.org/api_docs/python/tf/grad_pass_through

Creates a grad-pass-through op with the forward behavior provided in f.

Function Signatures

```
tf.grad_pass_through( f )  
  
x = tf.Variable(1.0, name="x") z = tf.Variable(3.0, name="z")  
with tf.GradientTape() as tape: # y will evaluate to 9.0 y =  
    tf.grad_pass_through(x.assign)(z**2) # grads will evaluate to  
    6.0 grads = tape.gradient(y, z)  
  
x = ... # Some scalar value # A moving average object, we  
don't need to know how this is implemented moving_average =  
MovingAverage() with backprop.GradientTape() as tape: #  
mavg_x will evaluate to the current running average value  
mavg_x = tf.grad_pass_through(moving_average)(x) grads =  
tape.gradient(mavg_x, x) # grads will evaluate to 1.0
```

Code Examples

```
tf.grad_pass_through(  
    f  
)
```

```
tf.grad_pass_through(  
f  
)
```

```
x = tf.Variable(1.0, name="x")  
z = tf.Variable(3.0, name="z")  
with tf.GradientTape() as tape:  
# y will evaluate to 9.0  
y = tf.grad_pass_through(x.assign)(z**2)  
# grads will evaluate to 6.0  
grads = tape.gradient(y, z)
```

```
x = tf.Variable(1.0, name="x")  
z = tf.Variable(3.0, name="z")  
with tf.GradientTape() as tape:  
# y will evaluate to 9.0  
y = tf.grad_pass_through(x.assign)(z**2)  
# grads will evaluate to 6.0  
grads = tape.gradient(y, z)
```

```
x = ... # Some scalar value  
# A moving average object, we don't need to know how this is  
# implemented  
moving_average = MovingAverage()  
with backprop.GradientTape() as tape:  
# mavg_x will evaluate to the current running average value  
mavg_x = tf.grad_pass_through(moving_average)(x)  
grads = tape.gradient(mavg_x, x) # grads will evaluate to 1.0
```

```
x = ... # Some scalar value
# A moving average object, we don't need to know how this is
implemented
moving_average = MovingAverage()
with backprop.GradientTape() as tape:
# mavg_x will evaluate to the current running average value
mavg_x = tf.grad_pass_through(moving_average)(x)
grads = tape.gradient(mavg_x, x) # grads will evaluate to 1.0
```

Documentation

Creates a grad-pass-through op with the forward behavior provided in f.

View aliases

Compat aliases for migration

See

Migration guide for
more details.

`tf.compat.v1.grad_pass_through`

Use this function to wrap any op, maintaining its behavior in the forward pass, but replacing the original op in the backward graph with an identity. For example:

Another example is a 'differentiable' moving average approximation, where gradients are allowed to flow into the last value fed to the moving average, but the moving average is still used for the forward pass:

Returns

