

tf.group Stay organized with collections

Save and categorize content based on your preferences.

https://www.tensorflow.org/api_docs/python/tf/group

Create an op that groups multiple operations.

Function Signatures

```
tf.group( *inputs, **kwargs )
```

Code Examples

```
tf.group(  
    *inputs, **kwargs  
)
```

```
tf.group(  
    *inputs, **kwargs  
)
```

```
with tf.control_dependencies([a, b]):  
    c = tf.no_op()
```

```
with tf.control_dependencies([a, b]):  
    c = tf.no_op()
```

Documentation

Create an op that groups multiple operations.

View aliases

Compat aliases for migration

See

Migration guide for
more details.

`tf.compat.v1.group`

Used in the notebooks

- Migrating model checkpoints
 - Estimators
 - Validating correctness & numerical equivalence
 - Wiki40B Language Models

When this op finishes, all ops in inputs have finished. This op has no output.

When operating in a v1-style graph context, ops are not executed in the same order as specified in the code; TensorFlow will attempt to execute ops in parallel or in an order convenient to the result it is computing. `tf.group` allows you to request that one or more results finish before execution continues.

`tf.group` creates a single op (of type `NoOp`), and then adds appropriate control dependencies. Thus, `c = tf.group(a, b)` will compute the same graph as this:

See also `tf.tuple` and `tf.control_dependencies`.

Returns

Raises