

tf.identity Stay organized with collections Save and categorize content based on your preferences.

https://www.tensorflow.org/api_docs/python/tf/identity

Return a Tensor with the same shape and contents as input.

Function Signatures

```
tf.identity( input, name=None )  
a = tf.constant([0.78])  
a_identity = tf.identity(a)  
a.numpy()
```

Code Examples

```
tf.identity(  
  input, name=None  
)
```

```
tf.identity(  
  input, name=None  
)
```

```
a = tf.constant([0.78])  
a_identity = tf.identity(a)  
a.numpy()  
array([0.78], dtype=float32)  
a_identity.numpy()  
array([0.78], dtype=float32)
```

```
a = tf.constant([0.78])
```

```
a_identity = tf.identity(a)
```

```
array([0.78], dtype=float32)
```

```
a_identity.numpy()
```

Documentation

Return a Tensor with the same shape and contents as input.

View aliases

Compat aliases for migration

See

Migration guide for
more details.

`tf.compat.v1.identity`

Used in the notebooks

- Migrate LoggingTensorHook and StopAtStepHook to Keras callbacks
- Substantial Undocumented Infection Facilitates the Rapid Dissemination of Novel Coronavirus (SARS-CoV2)

The return value is not the same Tensor as the original, but contains the same values. This operation is fast when used on the same device.

For example:

Calling `tf.identity` on a variable will make a Tensor that represents the value of that variable at the time it is called. This is equivalent to calling `.read_value()`.

This function can also be used to explicitly transfer tensors between devices. For example, to transfer a tensor in GPU memory back to host memory, one can use:

Returns

