

tf.meshgrid Stay organized with collections Save and categorize content based on your preferences.

https://www.tensorflow.org/api_docs/python/tf/meshgrid

Broadcasts parameters for evaluation on an N-D grid.

Function Signatures

```
tf.meshgrid( *args, **kwargs )
```

Code Examples

```
tf.meshgrid(  
    *args, **kwargs  
)
```

```
tf.meshgrid(  
    *args, **kwargs  
)
```

```
x = [1, 2, 3]  
y = [4, 5, 6]  
X, Y = tf.meshgrid(x, y)  
# X = [[1, 2, 3],  
#      [1, 2, 3],  
#      [1, 2, 3]]  
# Y = [[4, 4, 4],  
#      [5, 5, 5],  
#      [6, 6, 6]]
```

```
x = [1, 2, 3]  
y = [4, 5, 6]  
X, Y = tf.meshgrid(x, y)  
# X = [[1, 2, 3],  
#      [1, 2, 3],  
#      [1, 2, 3]]  
# Y = [[4, 4, 4],  
#      [5, 5, 5],  
#      [6, 6, 6]]
```

Documentation

Broadcasts parameters for evaluation on an N-D grid.

View aliases

Compat aliases for migration

See

Migration guide for
more details.

`tf.compat.v1.meshgrid`

Used in the notebooks

- Optimizers with Core APIs

Given N one-dimensional coordinate arrays **args*, returns a list outputs of N-D coordinate arrays for evaluating expressions on an N-D grid.

Notes:

`meshgrid` supports cartesian ('xy') and matrix ('ij') indexing conventions. When the indexing argument is set to 'xy' (the default), the broadcasting instructions for the first two dimensions are swapped.

Examples:

Calling `X, Y = meshgrid(x, y)` with the tensors

- indexing: Either 'xy' or 'ij' (optional, default: 'xy').
- name: A name for the operation (optional).

Returns

`## Raises`

