

tf.reverse Stay organized with collections Save and categorize content based on your preferences.

https://www.tensorflow.org/api_docs/python/tf/reverse

Reverses specific dimensions of a tensor.

Function Signatures

```
tf.reverse( tensor: Annotated[Any, TV_ReverseV2_T], axis:
Annotated[Any, TV_ReverseV2_Tidx], name=None ) ->
Annotated[Any, TV_ReverseV2_T]
```

Code Examples

```
tf.reverse(
tensor: Annotated[Any, TV_ReverseV2_T],
axis: Annotated[Any, TV_ReverseV2_Tidx],
name=None
) -> Annotated[Any, TV_ReverseV2_T]
```

```
tf.reverse(
tensor: Annotated[Any, TV_ReverseV2_T],
axis: Annotated[Any, TV_ReverseV2_Tidx],
name=None
) -> Annotated[Any, TV_ReverseV2_T]
```

```

# tensor 't' is [[[[ 0, 1, 2, 3],
#                  [ 4, 5, 6, 7],
#                  [ 8, 9, 10, 11]],
#                [[12, 13, 14, 15],
#                 [16, 17, 18, 19],
#                 [20, 21, 22, 23]]]]
# tensor 't' shape is [1, 2, 3, 4]
# 'dims' is [3] or 'dims' is [-1]
reverse(t, dims) ==> [[[[ 3, 2, 1, 0],
#                         [ 7, 6, 5, 4],
#                         [11, 10, 9, 8]],
#                       [[15, 14, 13, 12],
#                        [19, 18, 17, 16],
#                        [23, 22, 21, 20]]]]
# 'dims' is '[1]' (or 'dims' is '[-3]')
reverse(t, dims) ==> [[[[12, 13, 14, 15],
#                        [16, 17, 18, 19],
#                        [20, 21, 22, 23]
#                        [ 0, 1, 2, 3],
#                        [ 4, 5, 6, 7],
#                        [ 8, 9, 10, 11]]]]
# 'dims' is '[2]' (or 'dims' is '[-2]')
reverse(t, dims) ==> [[[[8, 9, 10, 11],
#                        [4, 5, 6, 7],
#                        [0, 1, 2, 3]]
#                       [[20, 21, 22, 23],
#                        [16, 17, 18, 19],
#                        [12, 13, 14, 15]]]]

```

```

# tensor 't' is [[[[ 0, 1, 2, 3],
#                  [ 4, 5, 6, 7],
#                  [ 8, 9, 10, 11]],
#                [[12, 13, 14, 15],
#                 [16, 17, 18, 19],
#                 [20, 21, 22, 23]]]]
# tensor 't' shape is [1, 2, 3, 4]
# 'dims' is [3] or 'dims' is [-1]
reverse(t, dims) ==> [[[[ 3, 2, 1, 0],
#                         [ 7, 6, 5, 4],
#                         [11, 10, 9, 8]],
#                       [[15, 14, 13, 12],
#                        [19, 18, 17, 16],
#                        [23, 22, 21, 20]]]]
# 'dims' is '[1]' (or 'dims' is '[-3]')
reverse(t, dims) ==> [[[[12, 13, 14, 15],
#                        [16, 17, 18, 19],
#                        [20, 21, 22, 23]
#                        [ 0, 1, 2, 3],
#                        [ 4, 5, 6, 7],
#                        [ 8, 9, 10, 11]]]]
# 'dims' is '[2]' (or 'dims' is '[-2]')
reverse(t, dims) ==> [[[[8, 9, 10, 11],
#                        [4, 5, 6, 7],
#                        [0, 1, 2, 3]]
#                       [[20, 21, 22, 23],
#                        [16, 17, 18, 19],
#                        [12, 13, 14, 15]]]]

```

Documentation

Reverses specific dimensions of a tensor.

View aliases

Compat aliases for migration

See

Migration guide for
more details.

`tf.compat.v1.manip.reverse`, `tf.compat.v1.reverse`, `tf.compat.v1.reverse_v2`

Used in the notebooks

- Ragged tensors

Given a tensor, and a `int32` tensor axis representing the set of dimensions of tensor to reverse. This operation reverses each dimension `i` for which there exists `j` s.t. `axis[j] == i`.

tensor can have up to 8 dimensions. The number of dimensions specified in axis may be 0 or more entries. If an index is specified more than once, a `InvalidArgument` error is raised.

For example:

Returns

