

tf.squeeze Stay organized with collections Save and categorize content based on your preferences.

https://www.tensorflow.org/api_docs/python/tf/squeeze

Removes dimensions of size 1 from the shape of a tensor.

Function Signatures

```
tf.squeeze( input, axis=None, name=None )  
# 't' is a tensor of shape [1, 2, 1, 3, 1, 1]  
tf.shape(tf.squeeze(t)) # [2, 3]  
# 't' is a tensor of shape [1, 2, 1, 3, 1, 1]  
tf.shape(tf.squeeze(t, [2, 4])) # [1, 2, 3, 1]
```

Code Examples

```
tf.squeeze(  
input, axis=None, name=None  
)
```

```
tf.squeeze(  
input, axis=None, name=None  
)
```

```
# 't' is a tensor of shape [1, 2, 1, 3, 1, 1]
tf.shape(tf.squeeze(t)) # [2, 3]
```

```
# 't' is a tensor of shape [1, 2, 1, 3, 1, 1]
tf.shape(tf.squeeze(t)) # [2, 3]
```

```
# 't' is a tensor of shape [1, 2, 1, 3, 1, 1]
tf.shape(tf.squeeze(t, [2, 4])) # [1, 2, 3, 1]
```

```
# 't' is a tensor of shape [1, 2, 1, 3, 1, 1]
tf.shape(tf.squeeze(t, [2, 4])) # [1, 2, 3, 1]
```

```
@tf.function
def func(x):
    print('x.shape:', x.shape)
    known_axes = [i for i, size in enumerate(x.shape) if size == 1]
    y = tf.squeeze(x, axis=known_axes)
    print('shape of tf.squeeze(x, axis=known_axes):', y.shape)
    y = tf.squeeze(x)
    print('shape of tf.squeeze(x):', y.shape)
    return 0
_ = func.get_concrete_function(tf.TensorSpec([None, 1, 2],
dtype=tf.int32))
# Output is.
# x.shape: (None, 1, 2)
# shape of tf.squeeze(x, axis=known_axes): (None, 2)
# shape of tf.squeeze(x):
```

```
@tf.function
def func(x):
    print('x.shape:', x.shape)
    known_axes = [i for i, size in enumerate(x.shape) if size == 1]
    y = tf.squeeze(x, axis=known_axes)
    print('shape of tf.squeeze(x, axis=known_axes):', y.shape)
    y = tf.squeeze(x)
    print('shape of tf.squeeze(x):', y.shape)
    return 0
_ = func.get_concrete_function(tf.TensorSpec([None, 1, 2],
dtype=tf.int32))
# Output is.
# x.shape: (None, 1, 2)
# shape of tf.squeeze(x, axis=known_axes): (None, 2)
# shape of tf.squeeze(x):
```

Documentation

Removes dimensions of size 1 from the shape of a tensor.

Used in the notebooks

- Logistic regression for binary classification with Core APIs
 - Multilayer perceptrons for digit recognition with Core APIs
 - Quickstart for the TensorFlow Core APIs
 - Unicode strings
 - Learned data compression
 - Generate music with an RNN
 - Simple audio recognition: Recognizing keywords
 - Intro to Autoencoders
 - Transfer learning with YAMNet for environmental sound classification

Given a tensor input, this operation returns a tensor of the same type with all dimensions of size 1 removed. If you don't want to remove all size 1 dimensions, you can remove specific size 1 dimensions by specifying axis.

For example:

Or, to remove specific size 1 dimensions:

Unlike the older op `tf.compat.v1.squeeze`, this op does not accept a deprecated `squeeze_dims` argument.

Returns

Raises