

tf.tile Stay organized with collections

Save and categorize content based on your preferences.

https://www.tensorflow.org/api_docs/python/tf/tile

Constructs a tensor by tiling a given tensor.

Function Signatures

```
tf.tile( input: Annotated[Any, TV_Tile_T], multiples:
Annotated[Any, TV_Tile_Tmultiples], name=None ) ->
Annotated[Any, TV_Tile_T]
```

Code Examples

```
tf.tile(
input: Annotated[Any, TV_Tile_T],
multiples: Annotated[Any, TV_Tile_Tmultiples],
name=None
) -> Annotated[Any, TV_Tile_T]
```

```
tf.tile(
input: Annotated[Any, TV_Tile_T],
multiples: Annotated[Any, TV_Tile_Tmultiples],
name=None
) -> Annotated[Any, TV_Tile_T]
```

```
a = tf.constant([[1,2,3],[4,5,6]], tf.int32)
b = tf.constant([1,2], tf.int32)
tf.tile(a, b)

c = tf.constant([2,1], tf.int32)
tf.tile(a, c)

d = tf.constant([2,2], tf.int32)
tf.tile(a, d)
```

```
a = tf.constant([[1,2,3],[4,5,6]], tf.int32)
```

```
b = tf.constant([1,2], tf.int32)
```

```
tf.tile(a, b)
```

```
array([[1, 2, 3, 1, 2, 3],
```

Documentation

Constructs a tensor by tiling a given tensor.

View aliases

Compat aliases for migration

See

Migration guide for
more details.

`tf.compat.v1.manip.tile`, `tf.compat.v1.tile`

Used in the notebooks

- Better performance with the `tf.data` API
 - Ragged tensors
 - Understanding masking & padding
 - Time series forecasting
 - Calculate gradients
 - Quantum data
 - Parametrized Quantum Circuits for Reinforcement Learning
 - A Tutorial on Multi-Armed Bandits with Per-Arm Features

This operation creates a new tensor by replicating input multiples times. The output tensor's *i*'th dimension has `input.dims(i) * multiples[i]` elements, and the values of input are replicated `multiples[i]` times along the *i*'th dimension. For example, tiling `[a b c d]` by `[2]` produces `[a b c d a b c d]`.

Returns

