

tf.AggregationMethod Stay organized with collections Save and categorize content based on your preferences.

https://www.tensorflow.org/api_docs/python/tf/AggregationMethod

A class listing aggregation methods used to combine gradients.

Code Examples

```
@tf.function
def example():
    x = tf.constant(1.0)
    y = x * 2.0
    z = y + y + y + y
    return tf.gradients(z, [x, y],
        aggregation_method=tf.AggregationMethod.EXPERIMENTAL_ACCUMULATE_N)
example()
[,
]
```

```
@tf.function
```

```
def example():
```

```
    x = tf.constant(1.0)
```

```
    y = x * 2.0
```

```
    z = y + y + y + y
```

```
    return tf.gradients(z, [x, y],
```

```
        aggregation_method=tf.AggregationMethod.EXPERIMENTAL_ACCUMULATE_N)
```

Documentation

A class listing aggregation methods used to combine gradients.

View aliases

Compat aliases for migration

See

Migration guide for
more details.

`tf.compat.v1.AggregationMethod`

Computing partial derivatives can require aggregating gradient contributions. This class lists the various methods that can be used to combine gradients in the graph.

The following aggregation methods are part of the stable API for aggregating gradients:

- **ADD_N**: All of the gradient terms are summed as part of one

operation using the "AddN" op (see `tf.add_n`). This method has the property that all gradients must be ready and buffered separately in memory before any aggregation is performed.

- **DEFAULT**: The system-chosen default aggregation method.

The following aggregation methods are experimental and may not be supported in future releases:

- **EXPERIMENTAL_TREE**: Gradient terms are summed in pairs using

the "AddN" op. This method of summing gradients may reduce performance, but it can improve memory utilization because the gradients can be released earlier.

- `EXPERIMENTAL_ACCUMULATE_N`: Same as `EXPERIMENTAL_TREE`.

Example usage when computing gradient:

`## Class Variables`