

tf.RegisterGradient Stay organized with collections Save and categorize content based on your preferences.

https://www.tensorflow.org/api_docs/python/tf/RegisterGradient

A decorator for registering the gradient function for an op type.

Function Signatures

```
tf.RegisterGradient( op_type )
```

Code Examples

```
tf.RegisterGradient(  
    op_type  
)
```

```
tf.RegisterGradient(  
    op_type  
)
```

```
@tf.RegisterGradient("Sub")  
def _sub_grad(unused_op, grad):  
    return grad, tf.negative(grad)
```

```
@tf.RegisterGradient("Sub")  
def _sub_grad(unused_op, grad):  
    return grad, tf.negative(grad)
```

```
__call__(  
    f: _T  
) -> _T
```

```
__call__(  
    f: _T  
) -> _T
```

Documentation

A decorator for registering the gradient function for an op type.

View aliases

Compat aliases for migration

See

Migration guide for
more details.

`tf.compat.v1.RegisterGradient`

This decorator is only used when defining a new op type. For an op with m inputs and n outputs, the gradient function is a function that takes the original Operation and n Tensor objects (representing the gradients with respect to each output of the op), and returns m Tensor objects (representing the partial gradients with respect to each input of the op).

For example, assuming that operations of type "Sub" take two inputs x and y , and return a single output $x - y$, the following gradient function would be registered:

The decorator argument `op_type` is the string type of an operation. This corresponds to the `OpDef.name` field for the proto that defines the operation.

Raises

Methods

`__call__`

[View source](#)

Registers the function `f` as gradient function for `op_type`.

