

tf.argsort Stay organized with collections Save and categorize content based on your preferences.

https://www.tensorflow.org/api_docs/python/tf/argsort

Returns the indices of a tensor that give its sorted order along an axis.

Function Signatures

```
tf.argsort( values, axis=-1, direction='ASCENDING',  
stable=False, name=None )  
sort_order = tf.argsort(values)  
sort_order.numpy()
```

Code Examples

```
tf.argsort(  
values, axis=-1, direction='ASCENDING', stable=False, name=None  
)
```

```
tf.argsort(  
values, axis=-1, direction='ASCENDING', stable=False, name=None  
)
```

```
values = [1, 10, 26.9, 2.8, 166.32, 62.3]  
sort_order = tf.argsort(values)  
sort_order.numpy()  
array([0, 3, 1, 2, 5, 4], dtype=int32)
```

```
values = [1, 10, 26.9, 2.8, 166.32, 62.3]
```

```
sort_order = tf.argsort(values)
```

```
sort_order.numpy()
```

```
array([0, 3, 1, 2, 5, 4], dtype=int32)
```

```
sorted = tf.gather(values, sort_order)  
assert tf.reduce_all(sorted == tf.sort(values))
```

Documentation

Returns the indices of a tensor that give its sorted order along an axis.

View aliases

Compat aliases for migration

See

Migration guide for
more details.

`tf.compat.v1.argsort`

Used in the notebooks

- MoViNet for streaming action recognition
 - Image Classification with TensorFlow Hub
 - Client-efficient large-model federated learning via ``federated_select`` and sparse aggregation

For a 1D tensor:

For higher dimensions, the output has the same shape as

values, but along the given axis, values represent the index of the sorted element in that slice of the tensor at the given position.

If `axis=-1` these indices can be used to apply a sort using `tf.gather`:

See also

- `tf.sort`: Sort along an axis.
 - `tf.math.top_k`: A partial sort that returns a fixed number of top values

and corresponding indices.

Returns

Raises