

tf.audio.decode_wav Stay organized with collections Save and categorize content based on your preferences.

https://www.tensorflow.org/api_docs/python/tf/audio/decode_wav

Decode a 16-bit PCM WAV file to a float tensor.

Function Signatures

```
tf.audio.decode_wav( contents: Annotated[Any,
_atypes.String], desired_channels: int = -1, desired_samples:
int = -1, name=None )
```

Code Examples

```
tf.audio.decode_wav(  
  contents: Annotated[Any, _atypes.String],  
  desired_channels: int = -1,  
  desired_samples: int = -1,  
  name=None  
)
```

```
tf.audio.decode_wav(  
  contents: Annotated[Any, _atypes.String],  
  desired_channels: int = -1,  
  desired_samples: int = -1,  
  name=None  
)
```

Documentation

Decode a 16-bit PCM WAV file to a float tensor.

View aliases

Compat aliases for migration

See

Migration guide for
more details.

`tf.compat.v1.audio.decode_wav`

Used in the notebooks

- Simple audio recognition: Recognizing keywords

- Transfer learning with YAMNet for environmental sound classification

The -32768 to 32767 signed 16-bit values will be scaled to -1.0 to 1.0 in float.

When `desired_channels` is set, if the input contains fewer channels than this then the last channel will be duplicated to give the requested number, else if the input has more channels than requested then the additional channels will be ignored.

If `desired_samples` is set, then the audio will be cropped or padded with zeroes to the requested length.

The first output contains a Tensor with the content of the audio samples. The lowest dimension will be the number of channels, and the second will be the number of samples. For example, a ten-sample-long stereo WAV file should give an output shape of [10, 2].

Returns