

tf.autograph.experimental.set_loop_options: Stay organized with collections Save and categorize content based on your preferences.

https://www.tensorflow.org/api_docs/python/tf/autograph/experimental/set_loop_options

Specifies additional arguments to be passed to the enclosing while_loop.

Function Signatures

```
tf.autograph.experimental.set_loop_options(  
    parallel_iterations=UNSPECIFIED, swap_memory=UNSPECIFIED,  
    maximum_iterations=UNSPECIFIED, shape_invariants=UNSPECIFIED  
)  
  
>>> @tf.function(autograph=True) ... def f(): ... n = 0 ...  
    for i in tf.range(10): ...  
        tf.autograph.experimental.set_loop_options(maximum_iterations=3)  
        ... n += 1 ... return n  
@tf.function(autograph=True)  
def f():
```

Code Examples

```
tf.autograph.experimental.set_loop_options(  
parallel_iterations=UNSPECIFIED,  
swap_memory=UNSPECIFIED,  
maximum_iterations=UNSPECIFIED,  
shape_invariants=UNSPECIFIED  
)
```

```
tf.autograph.experimental.set_loop_options(  
parallel_iterations=UNSPECIFIED,  
swap_memory=UNSPECIFIED,  
maximum_iterations=UNSPECIFIED,  
shape_invariants=UNSPECIFIED  
)
```

```
>>> @tf.function(autograph=True)  
... def f():  
...     n = 0  
...     for i in tf.range(10):  
...  
tf.autograph.experimental.set_loop_options(maximum_iterations=3)  
...     n += 1  
...     return n
```

```
>>> @tf.function(autograph=True)  
... def f():  
...     n = 0  
...     for i in tf.range(10):  
...  
tf.autograph.experimental.set_loop_options(maximum_iterations=3)  
...     n += 1  
...     return n
```

```
@tf.function(autograph=True)
def f():
    v = tf.constant((0,))
    for i in tf.range(3):
        tf.autograph.experimental.set_loop_options(
            shape_invariants=[(v, tf.TensorShape([None]))]
        )
    v = tf.concat((v, [i]), 0)
    return v
```

```
@tf.function(autograph=True)
```

```
v = tf.constant((0,))
```

Documentation

Specifies additional arguments to be passed to the enclosing `while_loop`.

View aliases

Compat aliases for migration

See

Migration guide for
more details.

`tf.compat.v1.autograph.experimental.set_loop_options`

The parameters apply to and only to the immediately enclosing loop. It only has effect if the loop is staged as a TF `while_loop`; otherwise the parameters have no effect.

Also see `tf.while_loop`.