

tf.bitwise.right_shift Stay organized with collections Save and categorize content based on your preferences.

https://www.tensorflow.org/api_docs/python/tf/bitwise/right_shift

Elementwise computes the bitwise right-shift of x and y.

Function Signatures

```
tf.bitwise.right_shift( x: Annotated[Any, TV_RightShift_T],  
y: Annotated[Any, TV_RightShift_T], name=None ) ->  
Annotated[Any, TV_RightShift_T]
```

Code Examples

```
tf.bitwise.right_shift(  
x: Annotated[Any, TV_RightShift_T],  
y: Annotated[Any, TV_RightShift_T],  
name=None  
) -> Annotated[Any, TV_RightShift_T]
```

```
tf.bitwise.right_shift(  
x: Annotated[Any, TV_RightShift_T],  
y: Annotated[Any, TV_RightShift_T],  
name=None  
) -> Annotated[Any, TV_RightShift_T]
```

```

import tensorflow as tf
from tensorflow.python.ops import bitwise_ops
import numpy as np
dtype_list = [tf.int8, tf.int16, tf.int32, tf.int64]
for dtype in dtype_list:
    lhs = tf.constant([-1, -5, -3, -14], dtype=dtype)
    rhs = tf.constant([5, 0, 7, 11], dtype=dtype)
    right_shift_result = bitwise_ops.right_shift(lhs, rhs)
    print(right_shift_result)
# This will print:
# tf.Tensor([-1 -5 -1 -1], shape=(4,), dtype=int8)
# tf.Tensor([-1 -5 -1 -1], shape=(4,), dtype=int16)
# tf.Tensor([-1 -5 -1 -1], shape=(4,), dtype=int32)
# tf.Tensor([-1 -5 -1 -1], shape=(4,), dtype=int64)
lhs = np.array([-2, 64, 101, 32], dtype=np.int8)
rhs = np.array([-1, -5, -3, -14], dtype=np.int8)
bitwise_ops.right_shift(lhs, rhs)
#

```

```

import tensorflow as tf
from tensorflow.python.ops import bitwise_ops
import numpy as np
dtype_list = [tf.int8, tf.int16, tf.int32, tf.int64]
for dtype in dtype_list:
    lhs = tf.constant([-1, -5, -3, -14], dtype=dtype)
    rhs = tf.constant([5, 0, 7, 11], dtype=dtype)
    right_shift_result = bitwise_ops.right_shift(lhs, rhs)
    print(right_shift_result)
# This will print:
# tf.Tensor([-1 -5 -1 -1], shape=(4,), dtype=int8)
# tf.Tensor([-1 -5 -1 -1], shape=(4,), dtype=int16)
# tf.Tensor([-1 -5 -1 -1], shape=(4,), dtype=int32)
# tf.Tensor([-1 -5 -1 -1], shape=(4,), dtype=int64)
lhs = np.array([-2, 64, 101, 32], dtype=np.int8)
rhs = np.array([-1, -5, -3, -14], dtype=np.int8)
bitwise_ops.right_shift(lhs, rhs)
#

```

Documentation

Elementwise computes the bitwise right-shift of x and y.

View aliases

Compat aliases for migration

See

Migration guide for
more details.

`tf.compat.v1.bitwise.right_shift`

Performs a logical shift for unsigned integer types, and an arithmetic shift for signed integer types.

If y is negative, or greater than or equal to than the width of x in bits the result is implementation defined.

Example:

`## Returns`