

tf.boolean_mask Stay organized with collections Save and categorize content based on your preferences.

https://www.tensorflow.org/api_docs/python/tf/boolean_mask

Apply boolean mask to tensor.

Function Signatures

```
tf.boolean_mask( tensor, mask, axis=None, name='boolean_mask'
)
0 < dim(mask) = K <= dim(tensor)
```

Code Examples

```
tf.boolean_mask(  
    tensor, mask, axis=None, name='boolean_mask'  
)
```

```
tf.boolean_mask(  
    tensor, mask, axis=None, name='boolean_mask'  
)
```

```
tensor = [0, 1, 2, 3] # 1-D example  
mask = np.array([True, False, True, False])  
tf.boolean_mask(tensor, mask)
```

```
tensor = [0, 1, 2, 3] # 1-D example
```

```
mask = np.array([True, False, True, False])
```

```
tf.boolean_mask(tensor, mask)
```

```
tensor = [[1, 2], [3, 4], [5, 6]] # 2-D example  
mask = np.array([True, False, True])  
tf.boolean_mask(tensor, mask)
```

Documentation

Apply boolean mask to tensor.

Numpy equivalent is `tensor[mask]`.

In general, $0 < \text{dim}(\text{mask}) = K \leq \text{dim}(\text{tensor})$, and mask's shape must match the first K dimensions of tensor's shape. We then have:

`boolean_mask(tensor, mask)[i, j1,...,jd] = tensor[i1,...,iK,j1,...,jd]`

where $(i1,...,iK)$ is the i th True entry of mask (row-major order).

The axis could be used with mask to indicate the axis to mask from.

In that case, $\text{axis} + \text{dim}(\text{mask}) \leq \text{dim}(\text{tensor})$ and mask's shape must match the first $\text{axis} + \text{dim}(\text{mask})$ dimensions of tensor's shape.

See also: `tf.ragged.boolean_mask`, which can be applied to both dense and ragged tensors, and can be used if you need to preserve the masked dimensions of tensor (rather than flattening them, as `tf.boolean_mask` does).

Examples:

Returns

Raises

Examples: