

tf.broadcast_static_shape Stay organized with collections Save and categorize content based on your preferences.

https://www.tensorflow.org/api_docs/python/tf/broadcast_static_shape

Computes the shape of a broadcast given known shapes.

Function Signatures

```
tf.broadcast_static_shape( shape_x, shape_y )
```

Code Examples

```
tf.broadcast_static_shape(  
    shape_x, shape_y  
)
```

```
tf.broadcast_static_shape(  
    shape_x, shape_y  
)
```

```
shape_x = tf.TensorShape([1, 2, 3])  
shape_y = tf.TensorShape([5, 1, 3])  
tf.broadcast_static_shape(shape_x, shape_y)  
TensorShape([5, 2, 3])
```

```
shape_x = tf.TensorShape([1, 2, 3])
```

```
shape_y = tf.TensorShape([5, 1, 3])
```

```
tf.broadcast_static_shape(shape_x, shape_y)
```

```
TensorShape([5, 2, 3])
```

Documentation

Computes the shape of a broadcast given known shapes.

View aliases

Compat aliases for migration

See

Migration guide for
more details.

`tf.compat.v1.broadcast_static_shape`

When `shape_x` and `shape_y` are fully known `TensorShapes` this computes a `TensorShape` which is the shape of the result of a broadcasting op applied in tensors of shapes `shape_x` and `shape_y`.

For example, if `shape_x` is `TensorShape([1, 2, 3])` and `shape_y` is `TensorShape([5, 1, 3])`, the result is a `TensorShape` whose value is `TensorShape([5, 2, 3])`.

This is useful when validating the result of a broadcasting operation when the tensors have statically known shapes.

Example:

`## Returns`

`## Raises`

