

tf.compat.forward_compatibility_horizon

Stay organized with collections Save and categorize content based on your preferences.

https://www.tensorflow.org/api_docs/python/tf/compat/forward_compatibility_horizon

Context manager for testing forward compatibility of generated graphs.

Function Signatures

```
tf.compat.forward_compatibility_horizon( year, month, day )  
if compat.forward_compatible(year=2018, month=08, day=01):  
    generate_graph_with_new_features() else:  
    generate_graph_so_older_binaries_can_consume_it()
```

Code Examples

```
@tf_contextlib.contextmanager  
tf.compat.forward_compatibility_horizon(  
    year, month, day  
)
```

```
@tf_contextlib.contextmanager
```

```
tf.compat.forward_compatibility_horizon(  
year, month, day  
)
```

```
if compat.forward_compatible(year=2018, month=08, day=01):  
    generate_graph_with_new_features()  
else:  
    generate_graph_so_older_binaries_can_consume_it()
```

```
if compat.forward_compatible(year=2018, month=08, day=01):  
    generate_graph_with_new_features()  
else:  
    generate_graph_so_older_binaries_can_consume_it()
```

```
from tensorflow.python.compat import compat  
def testMyNewFeature(self):  
    with compat.forward_compatibility_horizon(2018, 08, 02):  
        # Test that generate_graph_with_new_features() has an effect
```

```
from tensorflow.python.compat import compat  
def testMyNewFeature(self):  
    with compat.forward_compatibility_horizon(2018, 08, 02):  
        # Test that generate_graph_with_new_features() has an effect
```

Documentation

Context manager for testing forward compatibility of generated graphs.

View aliases

Compat aliases for migration

See

Migration guide for
more details.

`tf.compat.v1.compat.forward_compatibility_horizon`

See Version

compatibility.

To ensure forward compatibility of generated graphs (see `forward_compatible`) with older binaries, new features can be gated with:

However, when adding new features, one may want to unittest it before the forward compatibility window expires. This context manager enables such tests. For example:

```
## Yields
```