

tf.compat.forward_compatible Stay organized with collections Save and categorize content based on your preferences.

https://www.tensorflow.org/api_docs/python/tf/compat/forward_compatible

Return true if the forward compatibility window has expired.

Function Signatures

```
tf.compat.forward_compatible( year, month, day )  
def add(inputs, name=None): return gen_math_ops.add(inputs,  
name)
```

Code Examples

```
tf.compat.forward_compatible(  
year, month, day  
)
```

```
tf.compat.forward_compatible(  
year, month, day  
)
```

```
def add(inputs, name=None):  
    return gen_math_ops.add(inputs, name)
```

```
def add(inputs, name=None):  
    return gen_math_ops.add(inputs, name)
```

```
from tensorflow.python.compat import compat  
def add(inputs, name=None):  
    if compat.forward_compatible(year, month, day):  
        # Can use the awesome new implementation.  
        return gen_math_ops.my_new_awesome_add(inputs, name)  
    # To maintain forward compatibility, use the old implementation.  
    return gen_math_ops.add(inputs, name)
```

```
from tensorflow.python.compat import compat  
def add(inputs, name=None):  
    if compat.forward_compatible(year, month, day):  
        # Can use the awesome new implementation.  
        return gen_math_ops.my_new_awesome_add(inputs, name)  
    # To maintain forward compatibility, use the old implementation.  
    return gen_math_ops.add(inputs, name)
```

Documentation

Return true if the forward compatibility window has expired.

View aliases

Compat aliases for migration

See

Migration guide for
more details.

`tf.compat.v1.compat.forward_compatible`

See [Version compatibility](#).

Forward-compatibility refers to scenarios where the producer of a TensorFlow model (a `GraphDef` or `SavedModel`) is compiled against a version of the TensorFlow library newer than what the consumer was compiled against. The "producer" is typically a Python program that constructs and trains a model while the "consumer" is typically another program that loads and serves the model.

TensorFlow has been supporting a 3 week forward-compatibility window for programs compiled from source at HEAD.

For example, consider the case where a new operation `MyNewAwesomeAdd` is created with the intent of replacing the implementation of an existing Python wrapper - `tf.add`. The Python wrapper implementation should change from

something like:

Where year, month, and day specify the date beyond which binaries that consume a model are expected to have been updated to include the new operations. This date is typically at least 3 weeks beyond the date the code that adds the new operation is committed.

Returns