

tf.compat.v1.GraphDef Stay organized with collections Save and categorize content based on your preferences.

https://www.tensorflow.org/api_docs/python/tf/compat/v1/GraphDef

A protobuf containing the graph of operations.

Function Signatures

```
with tf.io.gfile.GFile('/tmp/graph.pb', 'rb') as f: graph_def
= tf.compat.v1.GraphDef() graph_def.ParseFromString(f.read())
tf.saved_model.load('/tmp/saved_model')
```

Code Examples

```
with tf.io.gfile.GFile('/tmp/graph.pb', 'rb') as f:
    graph_def = tf.compat.v1.GraphDef()
    graph_def.ParseFromString(f.read())
```

```
with tf.io.gfile.GFile('/tmp/graph.pb', 'rb') as f:
    graph_def = tf.compat.v1.GraphDef()
    graph_def.ParseFromString(f.read())
```

```
tf.saved_model.load('/tmp/saved_model')
```

```
tf.saved_model.load('/tmp/saved_model')
```

```
@tf.function
def f(x):
    return x
graph_def = f.get_concrete_function(1.).graph.as_graph_def()
print(graph_def)
```

```
@tf.function
```

Documentation

A protobuf containing the graph of operations.

Migrate to TF2

This API is not available in TensorFlow 2.x.

You should not need to use GraphDefs directly in TF2. To load GraphDefs in TF2, use SavedModel. The SavedModel contains the GraphDef.

Before:

After:

If you would like to create a GraphDef in TF2, use `tf.function` and `get_concrete_function`.

Description

Used in the notebooks

- Migrating your TFLite code to TF2

Attributes