

tf.compat.v1.GraphKeys Stay organized with collections Save and categorize content based on your preferences.

https://www.tensorflow.org/api_docs/python/tf/compat/v1/GraphKeys

Standard names to use for graph collections.

Documentation

Standard names to use for graph collections.

The standard library uses various well-known names to collect and retrieve values associated with a graph. For example, the `tf.Optimizer` subclasses default to optimizing the variables collected under `tf.GraphKeys.TRAINABLE_VARIABLES` if none is specified, but it is also possible to pass an explicit list of variables.

The following standard keys are defined:

- `GLOBAL_VARIABLES`: the default collection of `Variable` objects, shared

across distributed environment (model variables are subset of these). See `tf.compat.v1.global_variables` for more details.

Commonly, all `TRAINABLE_VARIABLES` variables will be in `MODEL_VARIABLES`,

and all `MODEL_VARIABLES` variables will be in `GLOBAL_VARIABLES`.

- `LOCAL_VARIABLES`: the subset of Variable objects that are local to each

machine. Usually used for temporarily variables, like counters.

- `MODEL_VARIABLES`: the subset of Variable objects that are used in the

model for inference (feed forward).

- `TRAINABLE_VARIABLES`: the subset of Variable objects that will

be trained by an optimizer. See
`tf.compat.v1.trainable_variables`
for more details.

- `SUMMARIES`: the summary Tensor objects that have been created in the

graph. See
`tf.compat.v1.summary.merge_all`
for more details.

- `QUEUE_RUNNERS`: the QueueRunner objects that are used to

produce input for a computation. See
`tf.compat.v1.train.start_queue_runners`
for more details.

- `MOVING_AVERAGE_VARIABLES`: the subset of Variable objects that will also

keep moving averages. See
`tf.compat.v1.moving_average_variables`

for more details.

- `REGULARIZATION_LOSSES`: regularization losses collected during graph

construction.

The following standard keys are defined, but their collections are not automatically populated as many of the others are:

- `WEIGHTS`
- `BIASES`
- `ACTIVATIONS`

Class Variables