

tf.compat.v1.Print Stay organized with collections Save and categorize content based on your preferences.

https://www.tensorflow.org/api_docs/python/tf/compat/v1/Print

Prints a list of tensors. (deprecated)

Function Signatures

```
tf.compat.v1.Print( input_, data, message=None, first_n=None,
                    summarize=None, name=None )
```

Code Examples

```
tf.compat.v1.Print(  
input_, data, message=None, first_n=None, summarize=None, name=None  
)
```

```
tf.compat.v1.Print(  
input_, data, message=None, first_n=None, summarize=None, name=None  
)
```

```
sess = tf.compat.v1.Session()  
with sess.as_default():  
    tensor = tf.range(10)  
    print_op = tf.print(tensor)  
    with tf.control_dependencies([print_op]):  
        out = tf.add(tensor, tensor)  
    sess.run(out)
```

```
sess = tf.compat.v1.Session()  
with sess.as_default():  
    tensor = tf.range(10)  
    print_op = tf.print(tensor)  
    with tf.control_dependencies([print_op]):  
        out = tf.add(tensor, tensor)  
    sess.run(out)
```

Documentation

Prints a list of tensors. (deprecated)

Migrate to TF2

This API is deprecated. Use `tf.print` instead. `tf.print` does not need the `input_` argument.

`tf.print` works in TF2 when executing eagerly and inside a `tf.function`.

In TF1-styled sessions, an explicit control dependency declaration is needed to execute the `tf.print` operation. Refer to the documentation of `tf.print` for more details.

Description

This is an identity op (behaves like `tf.identity`) with the side effect of printing data when evaluating.

Returns