

tf.compat.v1.TextLineReader Stay organized with collections Save and categorize content based on your preferences.

https://www.tensorflow.org/api_docs/python/tf/compat/v1/TextLineReader

A Reader that outputs the lines of a file delimited by newlines.

Function Signatures

```
tf.compat.v1.TextLineReader( skip_header_lines=None,  
name=None )
```

Code Examples

```
tf.compat.v1.TextLineReader(  
skip_header_lines=None, name=None  
)
```

```
tf.compat.v1.TextLineReader(  
skip_header_lines=None, name=None  
)
```

```
num_records_produced(  
    name=None  
)
```

```
num_records_produced(  
    name=None  
)
```

```
num_work_units_completed(  
    name=None  
)
```

```
num_work_units_completed(  
    name=None  
)
```

```
read(  
    queue, name=None  
)
```

```
read(  
    queue, name=None  
)
```

Documentation

A Reader that outputs the lines of a file delimited by newlines.

Inherits From: ReaderBase

Newlines are stripped from the output.

See ReaderBase for supported methods.

Attributes

Methods

num_records_produced

[View source](#)

Returns the number of records this reader has produced.

This is the same as the number of Read executions that have succeeded.

num_work_units_completed

[View source](#)

Returns the number of work units this reader has finished processing.

[View source](#)

Returns the next record (key, value) pair produced by a reader.

Will dequeue a work unit from queue if necessary (e.g. when the Reader needs to start reading from a new file since it has finished with the previous file).

read_up_to

[View source](#)

Returns up to `num_records` (key, value) pairs produced by a reader.

Will dequeue a work unit from queue if necessary (e.g., when the Reader needs to start reading from a new file since it has finished with the previous file).

It may return less than `num_records` even before the last batch.

[View source](#)

Restore a reader to its initial clean state.

restore_state

[View source](#)

Restore a reader to a previously saved state.

Not all Readers support being restored, so this can produce an Unimplemented error.

serialize_state

[View source](#)

Produce a string tensor that encodes the state of a reader.

Not all Readers support being serialized, so this can produce an Unimplemented error.

eager compatibility

Readers are not compatible with eager execution. Instead, please use `tf.data` to get data into your model.