

tf.compat.v1.boolean_mask Stay organized with collections Save and categorize content based on your preferences.

https://www.tensorflow.org/api_docs/python/tf/compat/v1/boolean_mask

Apply boolean mask to tensor.

Function Signatures

```
tf.compat.v1.boolean_mask( tensor, mask, name='boolean_mask',  
axis=None )  
0 < dim(mask) = K <= dim(tensor)
```

Code Examples

```
tf.compat.v1.boolean_mask(  
    tensor, mask, name='boolean_mask', axis=None  
)
```

```
tf.compat.v1.boolean_mask(  
    tensor, mask, name='boolean_mask', axis=None  
)
```

```
# 1-D example  
tensor = [0, 1, 2, 3]  
mask = np.array([True, False, True, False])  
tf.boolean_mask(tensor, mask) # [0, 2]  
  
# 2-D example  
tensor = [[1, 2], [3, 4], [5, 6]]  
mask = np.array([True, False, True])  
tf.boolean_mask(tensor, mask) # [[1, 2], [5, 6]]
```

```
# 1-D example  
tensor = [0, 1, 2, 3]  
mask = np.array([True, False, True, False])  
tf.boolean_mask(tensor, mask) # [0, 2]  
  
# 2-D example  
tensor = [[1, 2], [3, 4], [5, 6]]  
mask = np.array([True, False, True])  
tf.boolean_mask(tensor, mask) # [[1, 2], [5, 6]]
```

Documentation

Apply boolean mask to tensor.

Numpy equivalent is `tensor[mask]`.

In general, $0 < \dim(\text{mask}) = K \leq \dim(\text{tensor})$, and mask's shape must match the first K dimensions of tensor's shape. We then have:

`boolean_mask(tensor, mask)[i, j1,...,jd] = tensor[i1,...,iK,j1,...,jd]`

where $(i1,...,iK)$ is the i th True entry of mask (row-major order).

The axis could be used with mask to indicate the axis to mask from.

In that case, $\text{axis} + \dim(\text{mask}) \leq \dim(\text{tensor})$ and mask's shape must match the first $\text{axis} + \dim(\text{mask})$ dimensions of tensor's shape.

See also: `tf.ragged.boolean_mask`, which can be applied to both dense and ragged tensors, and can be used if you need to preserve the masked dimensions of tensor (rather than flattening them, as `tf.boolean_mask` does).

Examples:

`## Returns`

`## Raises`