

tf.compat.v1.convert_to_tensor Stay organized with collections Save and categorize content based on your preferences.

https://www.tensorflow.org/api_docs/python/tf/compat/v1/convert_to_tensor

Converts the given value to a Tensor.

Function Signatures

```
tf.compat.v1.convert_to_tensor( value, dtype=None, name=None,
preferred_dtype=None, dtype_hint=None ) -> tf.Tensor
```

Code Examples

```
tf.compat.v1.convert_to_tensor(  
value, dtype=None, name=None, preferred_dtype=None, dtype_hint=None  
) -> tf.Tensor
```

```
tf.compat.v1.convert_to_tensor(  
value, dtype=None, name=None, preferred_dtype=None, dtype_hint=None  
) -> tf.Tensor
```

```
import numpy as np  
def my_func(arg):  
    arg = tf.convert_to_tensor(arg, dtype=tf.float32)  
    return tf.matmul(arg, arg) + arg  
# The following calls are equivalent.  
value_1 = my_func(tf.constant([[1.0, 2.0], [3.0, 4.0]]))  
value_2 = my_func([[1.0, 2.0], [3.0, 4.0]])  
value_3 = my_func(np.array([[1.0, 2.0], [3.0, 4.0]],  
dtype=np.float32))
```

```
import numpy as np  
def my_func(arg):  
    arg = tf.convert_to_tensor(arg, dtype=tf.float32)  
    return tf.matmul(arg, arg) + arg  
# The following calls are equivalent.  
value_1 = my_func(tf.constant([[1.0, 2.0], [3.0, 4.0]]))  
value_2 = my_func([[1.0, 2.0], [3.0, 4.0]])  
value_3 = my_func(np.array([[1.0, 2.0], [3.0, 4.0]],  
dtype=np.float32))
```

Documentation

Converts the given value to a Tensor.

This function converts Python objects of various types to Tensor objects. It accepts Tensor objects, numpy arrays, Python lists, and Python scalars. For example:

This function can be useful when composing a new operation in Python (such as `my_func` in the example above). All standard Python op constructors apply this function to each of their Tensor-valued inputs, which allows those ops to accept numpy arrays, Python lists, and scalars in addition to Tensor objects.

Returns

`## Raises`