

tf.compat.v1.data.make_initializable_iterator

Stay organized with collections Save and categorize content based on your preferences.

https://www.tensorflow.org/api_docs/python/tf/compat/v1/data/make_initializable_iterator

Creates an iterator for elements of dataset.

Function Signatures

```
tf.compat.v1.data.make_initializable_iterator( dataset:  
tf.compat.v1.data.Dataset, shared_name=None ) ->  
tf.compat.v1.data.Iterator
```

Code Examples

```
tf.compat.v1.data.make_initializable_iterator(  
dataset: tf.compat.v1.data.Dataset,  
shared_name=None  
) -> tf.compat.v1.data.Iterator
```

```
tf.compat.v1.data.make_initializable_iterator(  
dataset: tf.compat.v1.data.Dataset,  
shared_name=None  
) -> tf.compat.v1.data.Iterator
```

```
tf.compat.v1.data.Dataset
```

```
tf.compat.v1.data.Iterator
```

```
dataset = ...  
iterator = tf.compat.v1.data.make_initializable_iterator(dataset)  
# ...  
sess.run(iterator.initializer)
```

```
dataset = ...  
iterator = tf.compat.v1.data.make_initializable_iterator(dataset)  
# ...  
sess.run(iterator.initializer)
```

Documentation

Creates an iterator for elements of dataset.

Migrate to TF2

This is a legacy API for consuming dataset elements and should only be used during transition from TF 1 to TF 2. Note that using this API should be a transient state of your code base as there are in general no guarantees about the interoperability of TF 1 and TF 2 code.

In TF 2 datasets are Python iterables which means you can consume their elements using `for elem in dataset: ...` or by explicitly creating iterator via `iterator = iter(dataset)` and fetching its elements via `values = next(iterator)`.

Description

Returns

Raises