

tf.compat.v1.distributions.Laplace Stay organized with collections Save and categorize content based on your preferences.

https://www.tensorflow.org/api_docs/python/tf/compat/v1/distributions/Laplace

The Laplace distribution with location loc and scale parameters.

Function Signatures

```
tf.compat.v1.distributions.Laplace( loc, scale,  
validate_args=False, allow_nan_stats=True, name='Laplace' )  
pdf(x; mu, sigma) = exp(-|x - mu| / sigma) / Z Z = 2 sigma
```

Code Examples

```
tf.compat.v1.distributions.Laplace(  
loc,  
scale,  
validate_args=False,  
allow_nan_stats=True,  
name='Laplace'  
)
```

```
tf.compat.v1.distributions.Laplace(  
    loc,  
    scale,  
    validate_args=False,  
    allow_nan_stats=True,  
    name='Laplace'  
)
```

$$\text{pdf}(x; \mu, \sigma) = \exp(-|x - \mu| / \sigma) / Z$$
$$Z = 2 \sigma$$
$$\text{pdf}(x; \mu, \sigma) = \exp(-|x - \mu| / \sigma) / Z$$
$$Z = 2 \sigma$$

```
X ~ Laplace(loc=0, scale=1)  
Y = loc + scale * X
```

```
X ~ Laplace(loc=0, scale=1)  
Y = loc + scale * X
```

```
batch_shape_tensor(  
    name='batch_shape_tensor'  
)
```

```
batch_shape_tensor(  
    name='batch_shape_tensor'  
)
```

Documentation

The Laplace distribution with location `loc` and scale parameters.

Inherits From: Distribution

Mathematical details

The probability density function (pdf) of this distribution is,

where $\text{loc} = \mu$, $\text{scale} = \sigma$, and Z is the normalization constant.

Note that the Laplace distribution can be thought of two exponential distributions spliced together "back-to-back."

The Laplace distribution is a member of the location-scale family, i.e., it can be constructed as,

Raises

Attributes

Stats return +/- infinity when it makes sense. E.g., the variance of a Cauchy distribution is infinity. However, sometimes the statistic is undefined, e.g., if a distribution's pdf does not achieve a maximum within the support of the distribution, the mode is undefined. If the mean is undefined, then by definition the variance is undefined. E.g. the mean for Student's T for $\text{df} = 1$ is undefined (no clear way to say it is either + or - infinity), so the variance = $E[(X - \text{mean})^2]$ is also undefined.

May be partially defined or unknown.

The batch dimensions are indexes into independent, non-identical parameterizations of this distribution.

May be partially defined or unknown.

Currently this is one of the static instances
`distributions.FULLY_REPARAMETERIZED`
or `distributions.NOT_REPARAMETERIZED`.

Methods

`## batch_shape_tensor`

[View source](#)

Shape of a single sample from a single event index as a 1-D Tensor.

The batch dimensions are indexes into independent, non-identical parameterizations of this distribution.

[View source](#)

Cumulative distribution function.

Given random variable X , the cumulative distribution function cdf is:

[View source](#)

Creates a deep copy of the distribution.

covariance

[View source](#)

Covariance.

Covariance is (possibly) defined only for non-scalar-event distributions.

For example, for a length- k , vector-valued distribution, it is calculated as,

where Cov is a (batch of) $k \times k$ matrix, $0 \leq (i, j) < k$, and E denotes expectation.

Alternatively, for non-vector, multivariate distributions (e.g., matrix-valued, Wishart), Covariance shall return a (batch of) matrices under some vectorization of the events, i.e.,

where Cov is a (batch of) $k' \times k'$ matrices, $0 \leq (i, j) < k' = \text{reduce_prod}(\text{event_shape})$, and Vec is some function mapping indices of this distribution's event dimensions to indices of a length- k' vector.

cross_entropy

[View source](#)

Computes the (Shannon) cross entropy.

Denote this distribution (self) by P and the other distribution by Q . Assuming P, Q are absolutely continuous with respect to one another and permit densities $p(x) dx$ and $q(x) dx$, (Shanon) cross entropy is defined as:

where F denotes the support of the random variable $X \sim P$.

entropy

[View source](#)

Shannon entropy in nats.

event_shape_tensor

[View source](#)

Shape of a single sample from a single batch as a 1-D int32 Tensor.

is_scalar_batch

[View source](#)

Indicates that batch_shape == [].

is_scalar_event

[View source](#)

Indicates that event_shape == [].

kl_divergence

[View source](#)

Computes the Kullback--Leibler divergence.

Denote this distribution (self) by p and the other distribution by q . Assuming p, q are absolutely continuous with respect to reference measure r , the KL divergence is defined as:

where F denotes the support of the random variable $X \sim p$, $H[., .]$ denotes (Shanon) cross entropy, and $H[.]$ denotes (Shanon) entropy.

log_cdf

[View source](#)

Log cumulative distribution function.

Given random variable X , the cumulative distribution function cdf is:

Often, a numerical approximation can be used for $\log_cdf(x)$ that yields a more accurate answer than simply taking the logarithm of the cdf when $x \ll -1$.

log_prob

[View source](#)

Log probability density/mass function.

log_survival_function

[View source](#)

Log survival function.

Given random variable X , the survival function is defined:

Typically, different numerical approximations can be used for the log survival function, which are more accurate than $1 - cdf(x)$ when $x \gg 1$.

[View source](#)

[View source](#)

param_shapes

[View source](#)

Shapes of parameters given the desired shape of a call to `sample()`.

This is a class method that describes what key/value arguments are required to instantiate the given Distribution so that a particular shape is returned for that instance's call to `sample()`.

Subclasses should override class method `_param_shapes`.

param_static_shapes

[View source](#)

`param_shapes` with static (i.e. `TensorShape`) shapes.

This is a class method that describes what key/value arguments are required to instantiate the given Distribution so that a particular shape is returned for that instance's call to `sample()`. Assumes that the sample's shape is known statically.

Subclasses should override class method `_param_shapes` to return constant-valued tensors when constant values are fed.

[View source](#)

Probability density/mass function.

quantile

[View source](#)

Quantile function. Aka "inverse cdf" or "percent point function".

Given random variable X and p in $[0, 1]$, the quantile is:

sample

[View source](#)

Generate samples of the specified shape.

Note that a call to `sample()` without arguments will generate a single sample.

stddev

[View source](#)

Standard deviation.

Standard deviation is defined as,

where X is the random variable associated with this distribution, E denotes expectation, and `stddev.shape = batch_shape + event_shape`.

survival_function

[View source](#)

Survival function.

Given random variable X , the survival function is defined:

variance

[View source](#)

Variance.

Variance is defined as,

where X is the random variable associated with this distribution, E denotes expectation, and `Var.shape = batch_shape + event_shape`.