

Module: `tf.compat.v1.experimental` Stay organized with collections Save and categorize content based on your preferences.

https://www.tensorflow.org/api_docs/python/tf/compat/v1/experimental

Public API for `tf._api.v2.experimental` namespace

Documentation

Public API for `tf._api.v2.experimental` namespace

Modules

`extension_type` module: Public API for `tf._api.v2.experimental.extension_type` namespace

Classes

class `BatchableExtensionType`: An `ExtensionType` that can be batched and unbatched.

class `DynamicRaggedShape`: The shape of a ragged or dense tensor.

class `ExtensionType`: Base class for TensorFlow `ExtensionType` classes.

class `ExtensionTypeBatchEncoder`: Class used to encode and decode extension type values for batching.

class `ExtensionTypeSpec`: Base class for `tf.ExtensionType` `TypeSpec`.

class Optional: Represents a value that may or may not be present.

class RowPartition: Partitioning of a sequence of values into contiguous subsequences ("rows").

class StructuredTensor: A multidimensional collection of structures with the same schema.

Functions

async_clear_error(...): Clear pending operations and error statuses in async execution.

async_scope(...): Context manager for grouping async operations.

dispatch_for_api(...): Decorator that overrides the default implementation for a TensorFlow API.

dispatch_for_binary_elementwise_apis(...): Decorator to override default implementation for binary elementwise APIs.

dispatch_for_binary_elementwise_assert_apis(...): Decorator to override default implementation for binary elementwise assert APIs.

dispatch_for_unary_elementwise_apis(...): Decorator to override default implementation for unary elementwise APIs.

enable_strict_mode(...): If called, enables strict mode for all behaviors.

function_executor_type(...): Context manager for setting the executor of eager defined functions.

output_all_intermediates(...): Whether to output all intermediates from functional control flow ops.

register_filesystem_plugin(...): Loads a TensorFlow FileSystem plugin.

unregister_dispatch_for(...): Unregisters a function that was registered with

@dispatch_for_*

Other Members

8-bit float with 4 exponent bits and 3 mantissa bits, with extended finite range. This type has no representation for inf, and only two NaN values: 0xFF for negative NaN, and 0x7F for positive NaN.

8-bit float with 5 exponent bits and 2 mantissa bits.

Signed 4-bit integer.

Unsigned 4-bit integer.