

tf.compat.v1.flags.BooleanFlag Stay organized with collections Save and categorize content based on your preferences.

https://www.tensorflow.org/api_docs/python/tf/compat/v1/flags/BooleanFlag

Basic boolean flag.

Function Signatures

```
tf.compat.v1.flags.BooleanFlag( name: Text, default:
Union[Optional[bool], Text], help: Optional[Text],
short_name: Optional[Text] = None, **args ) -> None
```

Code Examples

```
tf.compat.v1.flags.BooleanFlag(
name: Text,
default: Union[Optional[bool], Text],
help: Optional[Text],
short_name: Optional[Text] = None,
**args
) -> None
```

```
tf.compat.v1.flags.BooleanFlag(  
    name: Text,  
    default: Union[Optional[bool], Text],  
    help: Optional[Text],  
    short_name: Optional[Text] = None,  
    **args  
) -> None
```

```
flag_type() -> Text
```

```
flag_type() -> Text
```

```
parse(  
    argument: Union[Text, Optional[_T]]  
) -> None
```

```
parse(  
    argument: Union[Text, Optional[_T]]  
) -> None
```

```
serialize() -> Text
```

```
serialize() -> Text
```

Documentation

Basic boolean flag.

Inherits From: Flag

Boolean flags do not take any arguments, and their value is either True (1) or False (0). The false value is specified on the command line by prepending the word 'no' to either the long or the short flag name.

For example, if a Boolean flag was created whose long name was 'update' and whose short name was 'x', then this flag could be explicitly unset through either --nouupdate or --nox.

Attributes

Methods

flag_type

Returns a str that describes the type of the flag.

Parses string and sets flag value.

serialize

Serializes the flag.

unparse

__bool__

__eq__

Return self==value.

__ge__

Return a >= b. Computed by @total_ordering from (not a < b).

__gt__

Return $a > b$. Computed by `@total_ordering` from $(\text{not } a < b)$ and $(a \neq b)$.

__le__

Return $a \leq b$. Computed by `@total_ordering` from $(a < b)$ or $(a == b)$.

__lt__

Return self