

tf.compat.v1.flags.DEFINE_bool Stay organized with collections Save and categorize content based on your preferences.

https://www.tensorflow.org/api_docs/python/tf/compat/v1/flags/DEFINE_bool

Registers a boolean flag.

Function Signatures

```
tf.compat.v1.flags.DEFINE_bool( name, default, help,  
    flag_values=_flagvalues.FLAGS, module_name=None,  
    required=False, **args )
```

Code Examples

```
tf.compat.v1.flags.DEFINE_bool(  
    name,  
    default,  
    help,  
    flag_values=_flagvalues.FLAGS,  
    module_name=None,  
    required=False,  
    **args  
)
```

```
tf.compat.v1.flags.DEFINE_bool(  
    name,  
    default,  
    help,  
    flag_values=_flagvalues.FLAGS,  
    module_name=None,  
    required=False,  
    **args  
)
```

Documentation

Registers a boolean flag.

View aliases

Compat aliases for migration

See

Migration guide for
more details.

`tf.compat.v1.flags.DEFINE_boolean`

Such a boolean flag does not take an argument. If a user wants to specify a false value explicitly, the long option beginning with 'no' must be used: i.e. `--noflag`

This flag will have a value of `None`, `True` or `False`. `None` is possible if `default=None` and the user does not specify the flag on the command line.

Returns