

tf.compat.v1.flags.FLAGS Stay organized with collections Save and categorize content based on your preferences.

https://www.tensorflow.org/api_docs/python/tf/compat/v1/flags/FLAGS

Registry of :class:`~absl.flags.Flag` objects.

Function Signatures

```
tf.compat.v1.flags.FLAGS( *args, **kwargs )
```

Code Examples

```
tf.compat.v1.flags.FLAGS(  
    *args, **kwargs  
)
```

```
tf.compat.v1.flags.FLAGS(  
    *args, **kwargs  
)
```

```
FLAGS['longname'] = x    # register a new flag
```

```
FLAGS['longname'] = x    # register a new flag
```

```
FLAGS.longname  # parsed flag value  
FLAGS.x        # parsed flag value (short name)
```

```
FLAGS.longname  # parsed flag value  
FLAGS.x        # parsed flag value (short name)
```

```
argv = FLAGS(sys.argv)  # scan command line arguments
```

```
argv = FLAGS(sys.argv)  # scan command line arguments
```

Documentation

Registry of :class:~absl.flags.Flag objects.

A :class:FlagValues can then scan command line arguments, passing flag arguments through to the 'Flag' objects that it owns. It also provides easy access to the flag values. Typically only one :class:FlagValues object is needed by an application:
:const:FLAGS.

This class is heavily overloaded:

:class:Flag objects are registered via __setitem__::

The .value attribute of the registered :class:~absl.flags.Flag objects can be accessed as attributes of this :class:FlagValues object, through __getattr__. Both the long and short name of the original :class:~absl.flags.Flag objects can be used to access its value::

Command line arguments are scanned and passed to the registered :class:~absl.flags.Flag objects through the __call__ method. Unparsed arguments, including argv[0] (e.g. the program name) are returned::

The original registered :class:~absl.flags.Flag objects can be retrieved through the use of the dictionary-like operator, __getitem__::

The str() operator of a :class:absl.flags.FlagValues object provides help for all of the registered :class:~absl.flags.Flag objects.

