

tf.compat.v1.flags.Flag Stay organized with collections Save and categorize content based on your preferences.

https://www.tensorflow.org/api_docs/python/tf/compat/v1/flags/Flag

Information about a command-line flag.

Code Examples

```
tf.compat.v1.flags.Flag(  
    parser: _argument_parser.ArgumentParser[_T],  
    serializer: Optional[_argument_parser.ArgumentSerializer[_T]],  
    name: Text,  
    default: Union[Optional[_T], Text],  
    help_string: Optional[Text],  
    short_name: Optional[Text] = None,  
    boolean: bool = False,  
    allow_override: bool = False,  
    allow_override_cpp: bool = False,  
    allow_hide_cpp: bool = False,  
    allow_overwrite: bool = True,  
    allow_using_method_names: bool = False  
) -> None
```

```
tf.compat.v1.flags.Flag(  
  parser: _argument_parser.ArgumentParser[_T],  
  serializer: Optional[_argument_parser.ArgumentSerializer[_T]],  
  name: Text,  
  default: Union[Optional[_T], Text],  
  help_string: Optional[Text],  
  short_name: Optional[Text] = None,  
  boolean: bool = False,  
  allow_override: bool = False,  
  allow_override_cpp: bool = False,  
  allow_hide_cpp: bool = False,  
  allow_overwrite: bool = True,  
  allow_using_method_names: bool = False  
) -> None
```

```
flag_type() -> Text
```

```
flag_type() -> Text
```

```
parse(  
  argument: Union[Text, Optional[_T]]  
) -> None
```

```
parse(  
  argument: Union[Text, Optional[_T]]  
) -> None
```

```
serialize() -> Text
```

```
serialize() -> Text
```

Documentation

Information about a command-line flag.

The only public method of a Flag object is `:meth:parse`, but it is typically only called by a `:class:~absl.flags.FlagValues` object. The `:meth:parse` method is a thin wrapper around the `:meth:ArgumentParser.parse()` method. The parsed value is saved in `.value`, and the `.present` attribute is updated. If this flag was already present, an Error is raised.

`:meth:parse` is also called during `__init__` to parse the default value and initialize the `.value` attribute. This enables other python modules to safely use flags even if the `__main__` module neglects to parse the command line arguments. The `.present` attribute is cleared after `__init__` parsing. If the default value is set to None, then the `__init__` parsing step is skipped and the `.value` attribute is initialized to None.

Attributes

Methods

flag_type

Returns a str that describes the type of the flag.

Parses string and sets flag value.

serialize

Serializes the flag.

unparse

__bool__

__eq__

Return self==value.

__ge__

Return a >= b. Computed by @total_ordering from (not a < b).

__gt__

Return a > b. Computed by @total_ordering from (not a < b) and (a != b).

__le__

Return a <= b. Computed by @total_ordering from (a < b) or (a == b).

__lt__

Return self