

tf.compat.v1.flags.MultiFlag Stay organized with collections Save and categorize content based on your preferences.

https://www.tensorflow.org/api_docs/python/tf/compat/v1/flags/MultiFlag

A flag that can appear multiple time on the command-line.

Function Signatures

```
tf.compat.v1.flags.MultiFlag( *args, **kwargs )  
flag_type()
```

Code Examples

```
tf.compat.v1.flags.MultiFlag(  
    *args, **kwargs  
)
```

```
tf.compat.v1.flags.MultiFlag(  
    *args, **kwargs  
)
```

```
flag_type()
```

```
flag_type()
```

```
parse(  
    arguments: Union[Text, _T, Iterable[_T]]  
)
```

```
parse(  
    arguments: Union[Text, _T, Iterable[_T]]  
)
```

```
serialize() -> Text
```

```
serialize() -> Text
```

Documentation

A flag that can appear multiple time on the command-line.

Inherits From: Flag

The value of such a flag is a list that contains the individual values from all the appearances of that flag on the command-line.

See the doc for Flag for most behavior of this class. Only differences in behavior are described here:

- The default value may be either a single value or an iterable of values.

A single value is transformed into a single-item list of that value.

- The value of the flag is always a list, even if the option was

only supplied once, and even if the default value is a single value

The default value may be either a single value or an iterable of values.

A single value is transformed into a single-item list of that value.

The value of the flag is always a list, even if the option was only supplied once, and even if the default value is a single value

Attributes

Methods

flag_type

See base class.

Parses one or more arguments with the installed parser.

serialize

Serializes the flag.

unparse

__bool__

__eq__

Return self==value.

__ge__

Return a >= b. Computed by @total_ordering from (not a < b).

__gt__

Return a > b. Computed by @total_ordering from (not a < b) and (a != b).

__le__

Return a <= b. Computed by @total_ordering from (a < b) or (a == b).

__lt__

Return self