

tf.compat.v1.flags.flag_dict_to_args Stay organized with collections Save and categorize content based on your preferences.

https://www.tensorflow.org/api_docs/python/tf/compat/v1/flags/flag_dict_to_args

Convert a dict of values into process call parameters.

Function Signatures

```
tf.compat.v1.flags.flag_dict_to_args( flag_map: Dict[str, Any], multi_flags: Optional[Set[str]] = None ) -> Iterable[str]
```

Code Examples

```
tf.compat.v1.flags.flag_dict_to_args(  
    flag_map: Dict[str, Any], multi_flags: Optional[Set[str]] = None  
) -> Iterable[str]
```

```
tf.compat.v1.flags.flag_dict_to_args(  
    flag_map: Dict[str, Any], multi_flags: Optional[Set[str]] = None  
) -> Iterable[str]
```

Documentation

Convert a dict of values into process call parameters.

This method is used to convert a dictionary into a sequence of parameters for a binary that parses arguments using this module.

- If value is None, then only the name is emitted.
- If value is True, then only the name is emitted.
- If value is False, then only the name prepended with 'no' is

emitted.

- If value is a string then --name=value is emitted.
- If value is a collection, this will emit

--name=value1,value2,value3, unless the flag name is in multi_flags, in which case this will emit

--name=value1 --name=value2 --name=value3.

- Everything else is converted to string and passed as such.

If value is False, then only the name prepended with 'no' is emitted.

If value is a string then --name=value is emitted.

If value is a collection, this will emit

--name=value1,value2,value3, unless the flag name is in multi_flags, in which case this will emit

--name=value1 --name=value2 --name=value3.

Everything else is converted to string and passed as such.

`## Yields`