

tf.compat.v1.flags.register_validator

Stay organized with collections Save and categorize content based on your preferences.

https://www.tensorflow.org/api_docs/python/tf/compat/v1/flags/register_validator

Adds a constraint, which will be enforced during program execution.

Function Signatures

```
tf.compat.v1.flags.register_validator( flag_name, checker,  
message='Flag validation failed',  
flag_values=_flagvalues.FLAGS )  
raise flags.ValidationError(desired_error_message)
```

Code Examples

```
tf.compat.v1.flags.register_validator(  
    flag_name,  
    checker,  
    message='Flag validation failed',  
    flag_values=_flagvalues.FLAGS  
)
```

```
tf.compat.v1.flags.register_validator(  
    flag_name,  
    checker,  
    message='Flag validation failed',  
    flag_values=_flagvalues.FLAGS  
)
```

Documentation

Adds a constraint, which will be enforced during program execution.

The constraint is validated when flags are initially parsed, and after each change of the corresponding flag's value.

- input - A single positional argument: The value of the corresponding

flag (string, boolean, etc. This value will be passed to checker by the library).

- output - bool, True if validator constraint is satisfied.

If constraint is not satisfied, it should either return False or raise `flags.ValidationError(desired_error_message)`.

input - A single positional argument: The value of the corresponding flag (string, boolean, etc. This value will be passed to checker by the library).

output - bool, True if validator constraint is satisfied.

If constraint is not satisfied, it should either return False or raise `flags.ValidationError(desired_error_message)`.

Raises