

tf.compat.v1.get_session_handle Stay organized with collections Save and categorize content based on your preferences.

https://www.tensorflow.org/api_docs/python/tf/compat/v1/get_session_handle

Return the handle of data.

Function Signatures

```
tf.compat.v1.get_session_handle( data, name=None )
```

Code Examples

```
tf.compat.v1.get_session_handle(  
data, name=None  
)
```

```
tf.compat.v1.get_session_handle(  
data, name=None  
)
```

```
c = tf.multiply(a, b)  
h = tf.compat.v1.get_session_handle(c)  
h = sess.run(h)  
p, a = tf.compat.v1.get_session_tensor(h.handle, tf.float32)  
b = tf.multiply(a, 10)  
c = sess.run(b, feed_dict={p: h.handle})
```

```
c = tf.multiply(a, b)  
h = tf.compat.v1.get_session_handle(c)  
h = sess.run(h)  
p, a = tf.compat.v1.get_session_tensor(h.handle, tf.float32)  
b = tf.multiply(a, 10)  
c = sess.run(b, feed_dict={p: h.handle})
```

Documentation

Return the handle of data.

This is EXPERIMENTAL and subject to change.

Keep data "in-place" in the runtime and create a handle that can be used to retrieve data in a subsequent run().

Combined with `get_session_tensor`, we can keep a tensor produced in one run call in place, and use it as the input in a future run call.

Returns

Raises

Example: