

tf.compat.v1.lite.OpHint.OpHintArgumentTracker

Stay organized with collections Save and categorize content based on your preferences.

https://www.tensorflow.org/api_docs/python/tf/compat/v1/lite/OpHint/OpHintArgumentTracker

Conceptually tracks indices of arguments of "OpHint functions".

Function Signatures

```
tf.compat.v1.lite.OpHint.OpHintArgumentTracker(  
    function_name, unique_function_id, node_name_prefix,  
    attr_name, level=1, children_inputs_mappings=None )
```

Code Examples

```
tf.compat.v1.lite.OpHint.OpHintArgumentTracker(  
    function_name,  
    unique_function_id,  
    node_name_prefix,  
    attr_name,  
    level=1,  
    children_inputs_mappings=None  
)
```

```
tf.compat.v1.lite.OpHint.OpHintArgumentTracker(  
    function_name,  
    unique_function_id,  
    node_name_prefix,  
    attr_name,  
    level=1,  
    children_inputs_mappings=None  
)
```

```
add(  
    arg, tag=None, name=None, aggregate=None, index_override=None  
)
```

```
add(  
    arg, tag=None, name=None, aggregate=None, index_override=None  
)
```

Documentation

Conceptually tracks indices of arguments of "OpHint functions".

The inputs and arguments of these functions both use an instance of the class so they can have independent numbering.

Methods

[View source](#)

Return a wrapped tensor of an input tensor as an argument.