

tf.compat.v1.lookup.StaticVocabularyTable

Stay organized with collections Save and categorize content based on your preferences.

https://www.tensorflow.org/api_docs/python/tf/compat/v1/lookup/StaticVocabularyTable

String to Id table that assigns out-of-vocabulary keys to hash buckets.

Function Signatures

```
tf.compat.v1.lookup.StaticVocabularyTable( initializer,  
num_oov_buckets, lookup_key_dtype=None, name=None,  
experimental_is_anonymous=False )
```

Code Examples

```
tf.compat.v1.lookup.StaticVocabularyTable(  
    initializer,  
    num_oov_buckets,  
    lookup_key_dtype=None,  
    name=None,  
    experimental_is_anonymous=False  
)
```

```
tf.compat.v1.lookup.StaticVocabularyTable(  
    initializer,  
    num_oov_buckets,  
    lookup_key_dtype=None,  
    name=None,  
    experimental_is_anonymous=False  
)
```

```
init = tf.lookup.KeyValueTensorInitializer(  
    keys=tf.constant(['emerson', 'lake', 'palmer']),  
    values=tf.constant([0, 1, 2], dtype=tf.int64))  
table = tf.lookup.StaticVocabularyTable(  
    init,  
    num_oov_buckets=5)
```

```
init = tf.lookup.KeyValueTensorInitializer(  

```

```
keys=tf.constant(['emerson', 'lake', 'palmer']),  

```

```
values=tf.constant([0, 1, 2], dtype=tf.int64))  

```

```
table = tf.lookup.StaticVocabularyTable(  

```

Documentation

String to Id table that assigns out-of-vocabulary keys to hash buckets.

Inherits From: StaticVocabularyTable, TrackableResource

For example, if an instance of StaticVocabularyTable is initialized with a string-to-id initializer that maps:

The Vocabulary object will performs the following mapping:

- emerson -> 0
- lake -> 1
- palmer -> 2
- -> bucket_id, where bucket_id will be between 3 and

$3 + \text{num_oov_buckets} - 1 = 7$, calculated by:

$\text{hash()} \% \text{num_oov_buckets} + \text{vocab_size}$

If input_tensor is:

If initializer is None, only out-of-vocabulary buckets are used.

Example usage:

The hash function used for generating out-of-vocabulary buckets ID is Fingerprint64.

Note that the out-of-vocabulary bucket IDs always range from the table size up to $\text{size} + \text{num_oov_buckets} - 1$ regardless of the table values, which could cause unexpected collisions:

Raises

`## Attributes`

Methods

`## lookup`

[View source](#)

Looks up keys in the table, outputs the corresponding values.

It assigns out-of-vocabulary keys to buckets based in their hashes.

[View source](#)

Compute the number of elements in this table.

`__getitem__`

[View source](#)

Looks up keys in a table, outputs the corresponding values.