

tf.compat.v1.losses.cosine_distance

Stay organized with collections Save and categorize content based on your preferences.

https://www.tensorflow.org/api_docs/python/tf/compat/v1/losses/cosine_distance

Adds a cosine-distance loss to the training procedure. (deprecated arguments)

Function Signatures

```
tf.compat.v1.losses.cosine_distance( labels, predictions,  
axis=None, weights=1.0, scope=None,  
loss_collection=ops.GraphKeys.LOSSES,  
reduction=Reduction.SUM_BY_NONZERO_WEIGHTS, dim=None )  
(dim)
```

Code Examples

```
tf.compat.v1.losses.cosine_distance(  
    labels,  
    predictions,  
    axis=None,  
    weights=1.0,  
    scope=None,  
    loss_collection=ops.GraphKeys.LOSSES,  
    reduction=Reduction.SUM_BY_NONZERO_WEIGHTS,  
    dim=None  
)
```

```
tf.compat.v1.losses.cosine_distance(  
    labels,  
    predictions,  
    axis=None,  
    weights=1.0,  
    scope=None,  
    loss_collection=ops.GraphKeys.LOSSES,  
    reduction=Reduction.SUM_BY_NONZERO_WEIGHTS,  
    dim=None  
)
```

Documentation

Adds a cosine-distance loss to the training procedure. (deprecated arguments)

Note that the function assumes that predictions and labels are already unit-normalized.

Returns

`## Raises`

eager compatibility

The `loss_collection` argument is ignored when executing eagerly. Consider holding on to the return value or collecting losses via a `tf.keras.Model`.