

tf.compat.v1.losses.sigmoid_cross_entropy

Stay organized with collections Save and categorize content based on your preferences.

https://www.tensorflow.org/api_docs/python/tf/compat/v1/losses/sigmoid_cross_entropy

*Creates a cross-entropy loss using
tf.nn.sigmoid_cross_entropy_with_logits.*

Function Signatures

```
tf.compat.v1.losses.sigmoid_cross_entropy(  
    multi_class_labels, logits, weights=1.0, label_smoothing=0,  
    scope=None, loss_collection=ops.GraphKeys.LOSSES,  
    reduction=Reduction.SUM_BY_NONZERO_WEIGHTS )
```

Code Examples

```
tf.compat.v1.losses.sigmoid_cross_entropy(  
    multi_class_labels,  
    logits,  
    weights=1.0,  
    label_smoothing=0,  
    scope=None,  
    loss_collection=ops.GraphKeys.LOSSES,  
    reduction=Reduction.SUM_BY_NONZERO_WEIGHTS  
)
```

```
tf.compat.v1.losses.sigmoid_cross_entropy(  
    multi_class_labels,  
    logits,  
    weights=1.0,  
    label_smoothing=0,  
    scope=None,  
    loss_collection=ops.GraphKeys.LOSSES,  
    reduction=Reduction.SUM_BY_NONZERO_WEIGHTS  
)
```

```
new_multiclass_labels = multiclass_labels * (1 - label_smoothing)  
+ 0.5 * label_smoothing
```

```
new_multiclass_labels = multiclass_labels * (1 - label_smoothing)  
+ 0.5 * label_smoothing
```

Documentation

Creates a cross-entropy loss using `tf.nn.sigmoid_cross_entropy_with_logits`.

`weights` acts as a coefficient for the loss. If a scalar is provided, then the loss is simply scaled by the given value. If `weights` is a tensor of shape `[batch_size]`, then the loss weights apply to each corresponding sample.

If `label_smoothing` is nonzero, smooth the labels towards 1/2:

Returns

`## Raises`

eager compatibility

The `loss_collection` argument is ignored when executing eagerly. Consider holding on to the return value or collecting losses via a `tf.keras.Model`.