

tf.compat.v1.math.in_top_k Stay organized with collections Save and categorize content based on your preferences.

https://www.tensorflow.org/api_docs/python/tf/compat/v1/math/in_top_k

Says whether the targets are in the top K predictions.

Function Signatures

```
tf.compat.v1.math.in_top_k( predictions, targets, k,  
name=None )
```

Code Examples

```
tf.compat.v1.math.in_top_k(  
predictions, targets, k, name=None  
)
```

```
tf.compat.v1.math.in_top_k(  
predictions, targets, k, name=None  
)
```

Documentation

Says whether the targets are in the top K predictions.

View aliases

Compat aliases for migration

See

Migration guide for
more details.

`tf.compat.v1.nn.in_top_k`

This outputs a `batch_size` bool array, an entry `out[i]` is true if the prediction for the target class is finite (not `inf`, `-inf`, or `nan`) and among the top `k` predictions among all predictions for example `i`. Note that the behavior of `InTopK` differs from the `TopK` op in its handling of ties; if multiple classes have the same prediction value and straddle the top-`k` boundary, all of those classes are considered to be in the top `k`.

More formally, let

$\backslash(\text{predictions}_i\backslash)$ be the predictions for all classes for example `i`,

$\backslash(\text{targets}_i\backslash)$ be the target class for example `i`,

$\backslash(\text{out}_i\backslash)$ be the output for example `i`,

$\backslash(\text{out}_i = \text{predictions}_{\{i, \text{targets}_i\}} \text{ in TopKIncludingTies}(\text{predictions}_i)\backslash)$

Returns

