

tf.compat.v1.metrics.mean_absolute_error

Stay organized with collections Save and categorize content based on your preferences.

https://www.tensorflow.org/api_docs/python/tf/compat/v1/metrics/mean_absolute_error

Computes the mean absolute error between the labels and predictions.

Function Signatures

```
tf.compat.v1.metrics.mean_absolute_error( labels,  
predictions, weights=None, metrics_collections=None,  
updates_collections=None, name=None )
```

Code Examples

```
tf.compat.v1.metrics.mean_absolute_error(  
    labels,  
    predictions,  
    weights=None,  
    metrics_collections=None,  
    updates_collections=None,  
    name=None  
)
```

```
tf.compat.v1.metrics.mean_absolute_error(  
    labels,  
    predictions,  
    weights=None,  
    metrics_collections=None,  
    updates_collections=None,  
    name=None  
)
```

Documentation

Computes the mean absolute error between the labels and predictions.

The `mean_absolute_error` function creates two local variables, `total` and `count` that are used to compute the mean absolute error. This average is weighted by `weights`, and it is ultimately returned as `mean_absolute_error`: an idempotent operation that simply divides `total` by `count`.

For estimation of the metric over a stream of data, the function creates an `update_op` operation that updates these variables and returns the `mean_absolute_error`. Internally, an `absolute_errors` operation computes the absolute value of the differences between predictions and labels. Then `update_op` increments `total` with the reduced sum of the product of `weights` and `absolute_errors`, and it increments `count` with the reduced sum of `weights`

If `weights` is `None`, `weights` default to 1. Use `weights` of 0 to mask values.

Returns

Raises