

tf.compat.v1.metrics.mean_cosine_distance

Stay organized with collections Save and categorize content based on your preferences.

https://www.tensorflow.org/api_docs/python/tf/compat/v1/metrics/mean_cosine_distance

Computes the cosine distance between the labels and predictions.

Function Signatures

```
tf.compat.v1.metrics.mean_cosine_distance( labels,  
predictions, dim, weights=None, metrics_collections=None,  
updates_collections=None, name=None )
```

Code Examples

```
tf.compat.v1.metrics.mean_cosine_distance(  
    labels,  
    predictions,  
    dim,  
    weights=None,  
    metrics_collections=None,  
    updates_collections=None,  
    name=None  
)
```

```
tf.compat.v1.metrics.mean_cosine_distance(  
    labels,  
    predictions,  
    dim,  
    weights=None,  
    metrics_collections=None,  
    updates_collections=None,  
    name=None  
)
```

Documentation

Computes the cosine distance between the labels and predictions.

The `mean_cosine_distance` function creates two local variables, `total` and `count` that are used to compute the average cosine distance between predictions and labels. This average is weighted by weights, and it is ultimately returned as `mean_distance`, which is an idempotent operation that simply divides `total` by `count`.

For estimation of the metric over a stream of data, the function creates an `update_op` operation that updates these variables and returns the `mean_distance`.

If `weights` is `None`, `weights` default to 1. Use weights of 0 to mask values.

Returns

Raises