

# tf.compat.v1.metrics.precision Stay organized with collections Save and categorize content based on your preferences.

[https://www.tensorflow.org/api\\_docs/python/tf/compat/v1/metrics/precision](https://www.tensorflow.org/api_docs/python/tf/compat/v1/metrics/precision)

---

*Computes the precision of the predictions with respect to the labels.*

## Function Signatures

---

```
tf.compat.v1.metrics.precision( labels, predictions,  
weights=None, metrics_collections=None,  
updates_collections=None, name=None )
```

## Code Examples

---

```
tf.compat.v1.metrics.precision(  
    labels,  
    predictions,  
    weights=None,  
    metrics_collections=None,  
    updates_collections=None,  
    name=None  
)
```

```
tf.compat.v1.metrics.precision(  
    labels,  
    predictions,  
    weights=None,  
    metrics_collections=None,  
    updates_collections=None,  
    name=None  
)
```

# Documentation

---

Computes the precision of the predictions with respect to the labels.

## Used in the notebooks

- Exploring the TF-Hub CORD-19 Swivel Embeddings

The precision function creates two local variables, `true_positives` and `false_positives`, that are used to compute the precision. This value is ultimately returned as `precision`, an idempotent operation that simply divides `true_positives` by the sum of `true_positives` and `false_positives`.

For estimation of the metric over a stream of data, the function creates an `update_op` operation that updates these variables and returns the precision. `update_op` weights each prediction by the corresponding value in `weights`.

If `weights` is `None`, `weights` default to 1. Use `weights` of 0 to mask values.

## Returns

**## Raises**